



UNIDIRECTIONAL AIR FLOW

1-way cassette



Highlights

- Small capacities available starting from 2.2 kW
- Quiet operation
- External fresh air supply possible



1-way cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Suitable for long, narrow spaces with large window fronts. Available in six power levels from 2.2 to 7.1 kW.



Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated (4.5 to 7.1 kW models)
- External receiver kit for infrared remote control possible (2.2 to 3.6 kW models)
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power blackout



1-way cassette

Technical data			MMU-AP0074YH1-E
Cooling capacity	kW	❄️	2,20
Power consumption (min./nom./max.)	kW	❄️	0,053
Heating capacity	kW	🔥	2,50
Power consumption (min./nom./max.)	kW	🔥	0,053
Airflow	m ³ /h		540
Sound pressure level (low/med/high)	dB(A)	❄️	34/39/42
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1/50
Running current	A	❄️	0,24
Running current	A	🔥	0,24
Refrigerant			R410A
Dimensions (HxWxD)	mm		235 x 850 x 400
Weight	kg		22
Panel dimensions (HxWxD)	mm		18 x 1050 x 470
Panel weight	kg		3,5

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here: In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.

