




HIGH CAPACITY FLEXIBILITY

2-way cassette SMMSu



Highlights

- Wide performance spectrum
- Quiet operation
- External fresh air supply possible



2-way cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series. Perfectly suited for long, narrow spaces. Available in eleven capacity levels from 2.2 to 16.0 kW.



Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-step fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Automatic restart after power blackout adjustable



2-way cassette SMMSu

| Technical data | | | MMU-UP0481WH-E |
|-------------------------------------|-----------|----|------------------|
| Cooling capacity | kW | ❄️ | 14,00 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,088 |
| Heating capacity | kW | 🔥 | 16,00 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,088 |
| Airflow | m³/h | | 1230/1482/1800 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 37/40/43 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 37/40/43 |
| Liquid pipe diameter | mm (inch) | | 9,5 (3/8) |
| Suction gas pipe diameter | mm (inch) | | 15,9 (5/8) |
| Condensate pipe diameter | mm | | VP25 (25/32) |
| Power supply | V/Ph+N/Hz | | 220-240/1+N/50 |
| Running current | A | ❄️ | 0,57 |
| Running current | A | 🔥 | 0,57 |
| Current consumption (nom.) | A | | 0,57 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 345 x 1600 x 570 |
| Weight | kg | | 36 |
| Panel dimensions (HxWxD) | mm | | 20 x 1835 x 680 |
| Panel weight | kg | | 14 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.

