



## HIGH CAPACITY FLEXIBILITY

# 2-way cassette SMMSu



### Highlights

- Wide performance spectrum
- Quiet operation
- External fresh air supply possible



2-way cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series. Perfectly suited for long, narrow spaces. Available in eleven capacity levels from 2.2 to 16.0 kW.



### Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-step fan
- Quiet function
- Auto diagnostic system



### Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



### Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Automatic restart after power blackout adjustable



## 2-way cassette SMMSu

Technical data			MMU-UP0241WH-E
Cooling capacity	kW	❄️	7,10
Power consumption (min./nom./max.)	kW	❄️	0,054
Heating capacity	kW	🔥	8,00
Power consumption (min./nom./max.)	kW	🔥	0,054
Airflow	m³/h		738/840/1050
Sound pressure level (low/med/high)	dB(A)	❄️	33/35/38
Sound pressure level (low/med/high)	dB(A)	🔥	33/35/38
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,39
Running current	A	🔥	0,39
Current consumption (nom.)	A		0,39
Refrigerant			R410A
Dimensions (HxWxD)	mm		345 x 1180 x 570
Weight	kg		26
Panel dimensions (HxWxD)	mm		20 x 1415 x 680
Panel weight	kg		14

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Dust filter:** Washable filter against coarse contamination.



**Self-cleaning function:** Usage of condensate water for cleaning.

