



## THE 360° CLASSIC

### 4-way standard cassette SMMSu



#### Highlights

- Outstanding efficiency
- Two panels available for selection
- External fresh air supply possible



4-way standard cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series. Customized comfort, even for large spaces with high power requirements. Available in ten capacity levels from 2.8 to 16.0 kW.



#### Performance

- Very high energy efficiency
- Exhaust panel available for wide or direct air flow
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-step fan
- Quiet function
- Auto diagnostic system



#### Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all wired remote controls
- Automatic restart after power blackout adjustable



#### Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



## 4-way standard cassette SMMSu

Technical data			MMU-UP0121HP-E
Cooling capacity	kW	❄️	3,60
Power consumption (min./nom./max.)	kW	❄️	0,021
Heating capacity	kW	🔥	4,00
Power consumption (min./nom./max.)	kW	🔥	0,021
Airflow	m <sup>3</sup> /h		680/730/800
Sound pressure level (low/med/high)	dB(A)	❄️	30/29/27
Sound pressure level (low/med/high)	dB(A)	🔥	30/29/27
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,23
Running current	A	🔥	0,23
Current consumption (nom.)	A		0,23
Refrigerant			R410A
Dimensions (HxWxD)	mm		256 x 840 x 840
Weight	kg		18
Panel dimensions (HxWxD)	mm		30 x 950 x 950
Panel weight	kg		4

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Dust filter:** Washable filter against coarse contamination.



**Self-cleaning function:** Usage of condensate water for cleaning.

