TOSHIBA

## HIGH-EFFICIENCY 360° CLASSIC

# 4-way SMART standard cassette SMMSu

### Highlights

Outstanding efficiency
Customizable air distribution features
External fresh air supply possible
Occupancy-sensor option

Highly efficient 4-way cassette for RAV single-room systems for combination with VRF outdoor unit MiNi-SMMS-e, SMMS-e and SHRM-e series. Individual comfort, even for large spaces with high capacity requirements. Available in ten capacity sizes from 2.8 to 16.0 kW.

### Performance

- Very high energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 5-stage fan
- Individual louver function
- 360° airflow
- Quiet function
- Occupancy sensor option
- Auto diagnostic system

### Flexibility

- Optimum air distribution even in high rooms
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC

### Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all wired remote controls
- Additional functions available with remote control RBC-AMSU51-ES
- Automatic restart setting after power outage

HIGHER quality in LIFE

TOSHIBA

# 4-way SMART standard cassette SMMSu

| Technical data | | | MMU-UP0481H-E |
|---|---|---|---|
| Cooling capacity | kW | ❄ | 14,00 |
| Power consumption (min./nom./max.) | kW | ❄ | 0,135 |
| Heating capacity | kW | ☀ | 16,00 |
| Power consumption (min./nom./max.) | kW | ☀ | 0,135 |
| Airflow | $m^3/h$ | | 1368/1470/1740/1998/2262 |
| Sound pressure level (low/med/high) | dB(A) | ❄ | 33/39/46 |
| Sound pressure level (low/med/high) | dB(A) | ☀ | 33/39/46 |
| Sound power level | dB(A) | ❄ | 49/54/61 |
| Sound power level | dB(A) | ☀ | 49/54/61 |
| Liquid pipe diameter | mm (inch) | | 9,5 (3/8) |
| Suction gas pipe diameter | mm (inch) | | 15,9 (5/8) |
| Condensate pipe diameter | mm | | 25 |
| Power supply | V/Ph+N/Hz | | 220-240/1+N/50 |
| Running current | A | ❄ | 0,92 |
| Running current | A | ☀ | 0,96 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 319 x 840 x 840 |
| Weight | kg | | 25 |
| Panel dimensions (HxWxD) | mm | | 30 x 950 x 950 |
| Panel weight | kg | | 5,0 |

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

HIGHER quality in LIFE