TOSHIBA

HIGH-EFFICIENCY 360° CLASSIC

4-way SMART standard cassette SMMSu

Highlights

Outstanding efficiency
Customizable air distribution features
External fresh air supply possible
Occupancy-sensor option

Highly efficient 4-way cassette for RAV single-room systems for combination with VRF outdoor unit MiNi-SMMS-e, SMMS-e and SHRM-e series. Individual comfort, even for large spaces with high capacity requirements. Available in ten capacity sizes from 2.8 to 16.0 kW.

Performance

- Very high energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 5-stage fan
- Individual louver function
- 360° airflow
- Quiet function
- Occupancy sensor option
- Auto diagnostic system

Flexibility

- Optimum air distribution even in high rooms
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC

Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all wired remote controls
- Additional functions available with remote control RBC-AMSU51-ES
- Automatic restart setting after power outage

HIGHER quality in LIFE

TOSHIBA

4-way SMART standard cassette SMMSu

Technical data			MMU-UP0301H-E
Cooling capacity	kW	❄	9,00
Power consumption (min./nom./max.)	kW	❄	0,068
Heating capacity	kW	☀	10,00
Power consumption (min./nom./max.)	kW	☀	0,068
Airflow	m^3/h		1400/1450/1520/1770/1940
Sound pressure level (low/med/high)	dB(A)	❄	37/39/44
Sound pressure level (low/med/high)	dB(A)	☀	37/39/44
Sound power level	dB(A)	❄	51/53/58
Sound power level	dB(A)	☀	51/53/58
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄	0,57
Running current	A	☀	0,60
Refrigerant			R410A
Dimensions (HxWxD)	mm		319 x 840 x 840
Weight	kg		25
Panel dimensions (HxWxD)	mm		30 x 950 x 950
Panel weight	kg		5,0

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

HIGHER quality in LIFE