### **TOSHIBA**

### **EURO-GRID INNOVATION**

# 60x60 slim cassette





### Highlights

62 x 62 cm panel without grid overhang Customizable air distribution features Motion sensor option







4-way Euro-grid cassette for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Perfect look in the ceiling grid, available in six power levels from 1.7 to 5.6 kW.



#### Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 5-stage fan
- Individual louver function
- \_ 360° airflow
- \_ Motion sensor option
- \_ Auto diagnostic system



#### Flexibility

- 4 independent, controllable air control fins
- \_ Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- \_ Up to 4 indoor units can be connected to one outdoor unit
- Optional WiFi control via smartphone, tablet, or PC

#### Technical details

- Low unit overall height of only 256 mm
- \_ Slim exhaust panel with a height of only 12 mm
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage



# **TOSHIBA**

# 60x60 slim cassette

Technical data			MMU-AP0127MH-E
Cooling capacity	kW	*	3,60
Power consumption (min./nom./max.)	kW	*	0,027
Heating capacity	kW	*	4,00
Airflow	m³/h		402/594
Sound pressure level (low/med/high)	dB(A)	*	30/34/38
Sound power level	dB(A)	*	45/49/53
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1/50
Running current	А	*	0,25
Refrigerant			R410A
Dimensions (HxWxD)	mm		256 x 575 x 575
Weight	kg		15,0+2,5
Panel dimensions (HxWxD)	mm		12 x 620 x 620
Panel weight	kg		2,5

\* Cooling Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html



## **TOSHIBA**

In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



**Self-cleaning function:** Usage of condensate water for cleaning.

