



360° AIR COMFORT

60x60 slim cassette R32/R410A



Highlights

- Comfort air flow features
- 12 mm slim panel in pure white
- Remote control and optional motion sensor



Slim panel at just 62 x 62 cm to perfectly blend into the ceiling grid. The optional person recognition sensor saves energy when there are no people in the room.



Attractive and economical

- High (A++) energy efficiency for multi-systems
- High-performance heat exchanger
- Direct current hybrid inverter technology
- Exceptionally high efficiency in the partial load range
- Self-cleaning function
- Low-noise, 5-stage fan
- Individual louver function
- 360° airflow
- Motion sensor option



Flexibility

- Up to 5 indoor units can be connected to one outdoor unit
- 4 independent, controllable air control fins
- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Low unit overall height
- Slim exhaust panel with a height of only 12 mm
- Integrated drain pump with a discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with cable remote control
- Automatic restart setting after power outage



Easy operation

- Either infrared or cable remote control
- Off timer (0.5 to 12 hours)
- 24 hour ON/OFF timer
- Automatic mode
- Eco mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- Optional WiFi control via smartphone, tablet, or PC



Optional comfort and saving functions

- Comfort cable remote control optionally available
- Large, backlit display
- Weekly timer with 4 freely programmable settings per day
- 28 time programs per week
- Monitoring function
- Integrated temperature sensor



TOSHIBA

60x60 slim cassette R32/R410A

Technical data			RAS-M13U2MUVG-E
Cooling capacity	kW	❄️	3,70
Energy efficiency class		❄️	A++
Heating capacity	kW	🔥	5,00
Sound pressure level (low/med/high)	dB(A)	❄️	33/-/39
Sound pressure level (low/med/high)	dB(A)	🔥	32/-/39
Sound power level	dB(A)	❄️	45/53
Sound power level	dB(A)	🔥	45/53
Airflow	m³/h		620/430
Condensate pipe diameter	mm		VP20
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Refrigerant			R32
Dimensions (HxWxD)	mm		256 x 575 x 575
Weight	kg		15
Panel dimensions (HxWxD)	mm		16 x 620 x 620
Panel weight	kg		3

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Auto Mode: Automatic selection between cooling and heating.



Auto diagnostic: Check of system for flawless operation.



Quiet Mode: Whisper mode for the indoor unit.



Timer: Individual programming of on-/off times.



R32: Used refrigerant: R32.



Self-cleaning function: Usage of condensate water for cleaning.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Eco Mode: Energy saving function.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



Week Timer: Up to four settings per day and seven per week.

