



## PERFECT IN EURO-GRID

### 60x60 slim cassette R32/R410A



#### Highlights

- 620x620 panel without grid bar overhang
- Customizable air distribution features
- External fresh air supply possible
- Motion sensor option

Four-way Euro-grid cassette for RAV single-room systems for combination with Digital and Super Digital Inverter outdoor units for refrigerant R32 or R410A. Perfect look for ceiling grids, available in three power levels from 2.5 to 5.0 kW.



#### Highlights

- 620x620 panel without grid bar overhang
- Customizable air distribution features
- External fresh air supply possible
- Occupancy sensor option



#### Performance

- High energy efficiency (up to A++)
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 5-stage fan
- Individual louver function
- 360° airflow
- Motion sensor option
- Auto diagnostic system



#### Flexibility

- Compatible with R32 or R410A outdoor units
- Optimal air distribution up to room height of 3.5 m
- Easy-to-remove, washable dust filter
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



#### Technical details

- Low unit overall height of only 256 mm
- Slim exhaust panel with a height of only 12 mm
- Integrated drain pump with discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC link
- Automatic restart setting after power outage
- Optional redundancy box available



## 60x60 slim cassette R32/R410A / SET

Indoor unit			RAV-RM561MUT-E
Outdoor unit			RAV-GP561ATW-E
Cooling capacity	kW	❄️	5,00
Cooling range (min.-max.)	kW	❄️	1,20 - 5,60
Power consumption (min./nom./max.)	kW	❄️	0,19/1,56/1,97
Energy efficiency EER	W/W	❄️	3,21
Energy efficiency SEER		❄️	6,02
Energy efficiency class		❄️	A+
Annual electricity consumption	kWh/a	❄️	1237
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	5,60
Heating range (min.-max.)	kW	🔥	0,90 - 7,00
Power consumption (min./nom./max.)	kW	🔥	0,16/1,60/2,36
Energy efficiency COP	W/W	🔥	3,50
Energy efficiency SCOP		🔥	4,30
Energy efficiency class		🔥	A+
Annual electricity consumption	kWh/a	🔥	1237
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit			RAV-RM561MUT-E
Sound pressure level (low/med/high)	dB(A)	❄️	35/39/44
Sound pressure level (low/med/high)	dB(A)	🔥	35/39/44
Sound power level	dB(A)	❄️	50/54/59
Sound power level	dB(A)	🔥	50/54/59
Airflow	m³/h		546/672/798
Condensate pipe diameter	mm		VP20
Dimensions (HxWxD)	mm		256 x 575 x 575
Weight	kg		15
Panel dimensions (HxWxD)	mm		12 x 620 x 620
Panel weight	kg		3

❄️ Cooling 🔥 Heating



## 60x60 slim cassette R32/R410A / SET

Outdoor unit			RAV-GP561ATW-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		16
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	A		6,87
Current consumption (max.)	A		13,1
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m <sup>3</sup> /h		2250
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,35
Pre-charged up to	m		20
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 799 x 299
Weight	kg		45

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

