



PERFECT AMBIANCE

Ceiling unit R32/R410A



Highlights

- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital Inverter, Super Digital Inverter, and BIG Digital Inverter outdoor units for refrigerant R32 or R410A. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in five power levels from 3.6 to 12.5 kW.



Performance

- Extremely high energy efficiency (up to A+++)
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Compatible with R32 or R410A outdoor units
- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC link
- Automatic restart setting after power outage
- Optional redundancy box available



Ceiling unit R32/R410A / SET

Indoor unit			RAV-RM801CTP-E
Outdoor unit			RAV-GP801ATW-E
Cooling capacity	kW	❄️	7,10
Cooling range (min.-max.)	kW	❄️	1,90 - 8,00
Power consumption (min./nom./max.)	kW	❄️	0,26/1,60/3,17
Energy efficiency EER	W/W	❄️	4,44
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	8,00
Heating range (min.-max.)	kW	🔥	1,30 - 11,30
Power consumption (min./nom./max.)	kW	🔥	0,20/1,80/3,55
Energy efficiency COP	W/W	🔥	4,44
Outdoor temperature operating range (min.-max.)	°C	🔥	-27/ +15

Indoor unit			RAV-RM801CTP-E
Sound pressure level (low/med/high)	dB(A)	❄️	29/36/41
Sound pressure level (low/med/high)	dB(A)	🔥	29/36/41
Sound power level	dB(A)	❄️	44/51/56
Sound power level	dB(A)	🔥	44/51/56
Airflow	m³/h		1410
Condensate pipe diameter	mm		VP16
Dimensions (HxWxD)	mm		235 x 1270 x 690
Weight	kg		29

❄️ Cooling 🔥 Heating



Ceiling unit R32/R410A / SET

Outdoor unit			RAV-GP801ATW-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		16
Running current	A	❄️	7,17
Running current	A	🔥	7,98
Current consumption (nom.)	A		9,23
Current consumption (max.)	A		20,60
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m³/h		3180
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,3
Pre-charged up to	m		30
Added refrigerant charge	g/m		35
Dimensions (HxWxD)	mm		1050 x 1010 x 370
Weight	kg		74

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

