



PERFECT AMBIANCE

Ceiling unit SL R32



Highlights

- SL »speed line« feature update
- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven capacity sizes from 3.6 to 14.0 kW.



Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



Ceiling unit SL R32 / SET

Indoor unit			RAV-HM1101CTP-E
Outdoor unit			RAV-GP1103AT8P-E
Cooling capacity	kW	❄️	10,00
Cooling range (min.-max.)	kW	❄️	3,10 - 12,00
Outdoor temperature operating range (min.-max.)	°C	❄️	-20 / +52
Heating capacity	kW	🔥	11,20
Heating range (min.-max.)	kW	🔥	2,60 - 13,00
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit			RAV-HM1101CTP-E
Sound pressure level (low/med/high)	dB(A)	❄️	32/38/44
Sound pressure level (low/med/high)	dB(A)	🔥	32/38/44
Sound power level	dB(A)	❄️	47/53/59
Sound power level	dB(A)	🔥	47/53/59
Airflow	m³/h		1020/1350/1860
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		235 x 1586 x 690
Weight	kg		37,0

❄️ Cooling 🔥 Heating



Ceiling unit SL R32 / SET

Outdoor unit			RAV-GP1103AT8P-E
Power supply	V/Ph+N/Hz		380-415/3+N/50
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Sound power level	dB(A)	❄️	65
Sound power level	dB(A)	🔥	65
Sound pressure level (low/med/high)	dB(A)	❄️	50
Sound pressure level (low/med/high)	dB(A)	🔥	50
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		3
Pipe length (max.)	m		100
Height difference (max.)	m		30
Airflow	m³/h		7000
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		3,30
Pre-charged up to	m		30
Added refrigerant charge	g/m		40
Dimensions (HxWxD)	mm		1640 x 1100 x 460
Weight	kg		126

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

Accessories	Description
RBC-ASCU32Y-E	Compact wired remote control with sensor buttons
RBC-AXU31C-E	Infrared remote control + receiver kit for installation in ceiling unit
RBC-AMSU52-E	Wired comfort remote control PLUS
TCB-DP31CE	Drain pump, discharge head 600 mm, measured from lower edge of unit
TCB-KP14CPE	Elbow-kit, ISO14093 certified flares (required for drain pump), RAV: Sizes 4 + 5 / VRF: Sizes 15 + 18
TCB-KP24CPE	Elbow-kit, ISO14093 certified flares (required for drain pump), RAV: Sizes 8 + 16 / VRF: Sizes 24 to 56
TCB-PCUC2E	Control board for external control, alarms and messages
TCB-FF101URE2	Spigot flange for fresh air connection Ø 100 mm

