



PERFECT AMBIANCE

## Ceiling unit SL R32



### Highlights

- SL »speed line« feature update
- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven capacity sizes from 3.6 to 14.0 kW.



### Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



### Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



### Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



### SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



## Ceiling unit SL R32 / SET

Indoor unit	RAV-RM1401CTP-E		
Outdoor unit	RAV-GP1401AT-E1		
Cooling capacity	kW	❄️	12,50
Cooling range (min.-max.)	kW	❄️	3,10 - 14,00
Power consumption (min./nom./max.)	kW	❄️	0,55/3,58/3,97
Energy efficiency EER	W/W	❄️	3,49
Energy efficiency SEER		❄️	7,58
Annual electricity consumption	kWh/a	❄️	989
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	14,00
Heating range (min.-max.)	kW	🔥	2,60 - 16,50
Power consumption (min./nom./max.)	kW	🔥	0,41/3,59/4,40
Energy efficiency COP	W/W	🔥	3,90
Energy efficiency SCOP		🔥	4,71
Annual electricity consumption	kWh/a	🔥	2852
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit	RAV-RM1401CTP-E		
Sound pressure level (low/med/high)	dB(A)	❄️	35/41/46
Sound pressure level (low/med/high)	dB(A)	🔥	35/41/46
Sound power level	dB(A)	❄️	50/56/61
Sound power level	dB(A)	🔥	50/56/61
Airflow	m <sup>3</sup> /h		1200/1530/2040
Condensate pipe diameter	mm		VP20
Dimensions (HxWxD)	mm		235 x 1586 x 690
Weight	kg		35

❄️ Cooling 🔥 Heating



## Ceiling unit SL R32 / SET

Outdoor unit		RAV-GP1401AT-E1	
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		25
Communication line			H07RN-F 4G1,5
Running current	A	❄️	15,70 - 17,13
Running current	A	🔥	15,75 - 17,18
Current consumption (nom.)	A		15,70
Current consumption (max.)	A		21,6
Sound pressure level (low/med/high)	dB(A)	❄️	50
Sound pressure level (low/med/high)	dB(A)	🔥	51
Sound power level	dB(A)	❄️	67
Sound power level	dB(A)	🔥	68
Suction gas pipe diameter	mm (inch)		15,9 (3/4)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		75
Height difference (max.)	m		30
Airflow	m <sup>3</sup> /h		6960
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		3,10
Pre-charged up to	m		30
Added refrigerant charge	g/m		40
Dimensions (HxWxD)	mm		1550 x 1010 x 370
Weight	kg		104

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

