



PERFECT AMBIANCE

## Ceiling unit SL R32



### Highlights

- SL »speed line« feature update
- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven capacity sizes from 3.6 to 14.0 kW.



### Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



### Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



### Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



### SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



## Ceiling unit SL R32 / SET

Indoor unit	RAV-HM561CTP-E		
Outdoor unit	RAV-GP561ATW-E		
Cooling capacity	kW	❄️	5,00
Cooling range (min.-max.)	kW	❄️	1,20 - 5,60
Power consumption (min./nom./max.)	kW	❄️	0,19/1,37/1,98
Energy efficiency EER	W/W	❄️	3,65
Energy efficiency SEER		❄️	6,93
Energy efficiency class		❄️	A++
Annual electricity consumption	kWh/a	❄️	253
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	5,60
Heating range (min.-max.)	kW	🔥	0,90 - 7,40
Power consumption (min./nom./max.)	kW	🔥	0,16/1,39/2,67
Energy efficiency COP	W/W	🔥	4,03
Energy efficiency SCOP		🔥	4,73
Energy efficiency class		🔥	A++
Annual electricity consumption	kWh/a	🔥	1125
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit	RAV-HM561CTP-E		
Sound pressure level (low/med/high)	dB(A)	❄️	28/35/37
Sound pressure level (low/med/high)	dB(A)	🔥	28/35/37
Sound power level	dB(A)	❄️	43/50/52
Sound power level	dB(A)	🔥	43/50/52
Airflow	m <sup>3</sup> /h		540/720/900
Condensate pipe diameter	mm		VP20
Dimensions (HxWxD)	mm		235 x 950 x 690
Weight	kg		23

❄️ Cooling 🔥 Heating



## Ceiling unit SL R32 / SET

Outdoor unit			RAV-GP561ATW-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	☀️	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	☀️	65
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m <sup>3</sup> /h		2400
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,35
Pre-charged up to	m		20
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 799 x 299
Weight	kg		45

❄️ Cooling ☀️ Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

