



PERFECT AMBIANCE

Ceiling unit SL R32



Highlights

- SL »speed line« feature update
- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode

Under-ceiling unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven capacity sizes from 3.6 to 14.0 kW.



Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Easy installation via removable suspension fixtures
- Optional TCB-DP31CE drain pump available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



Ceiling unit SL R32 / SET

Indoor unit	RAV-HM801CTP-E		
Outdoor unit	RAV-GP801ATW-E		
Cooling capacity	kW	❄️	7,10
Cooling range (min.-max.)	kW	❄️	1,90 - 8,00
Power consumption (min./nom./max.)	kW	❄️	0,26/1,60/3,17
Energy efficiency EER	W/W	❄️	4,44
Energy efficiency SEER		❄️	8,35
Energy efficiency class		❄️	A++
Annual electricity consumption	kWh/a	❄️	298
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	8,00
Heating range (min.-max.)	kW	🔥	1,30 - 11,30
Power consumption (min./nom./max.)	kW	🔥	0,20/1,80/3,50
Energy efficiency COP	W/W	🔥	4,44
Energy efficiency SCOP		🔥	5,10
Energy efficiency class		🔥	A++
Annual electricity consumption	kWh/a	🔥	1401
Outdoor temperature operating range (min.-max.)	°C	🔥	-27/ +15

Indoor unit	RAV-HM801CTP-E		
Sound pressure level (low/med/high)	dB(A)	❄️	29/36/41
Sound pressure level (low/med/high)	dB(A)	🔥	29/36/41
Sound power level	dB(A)	❄️	44/51/62
Sound power level	dB(A)	🔥	44/51/62
Airflow	m ³ /h		750/1000/1410
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		235 x 1270 x 690
Weight	kg		29

❄️ Cooling 🔥 Heating



Ceiling unit SL R32 / SET

Outdoor unit			RAV-GP801ATW-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	☀️	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	☀️	65
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m ³ /h		3180
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,30
Pre-charged up to	m		30
Added refrigerant charge	g/m		35
Dimensions (HxWxD)	mm		1050 x 1010 x 370
Weight	kg		74

❄️ Cooling ☀️ Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

