



Perfect ambiance

Ceiling unit



Highlights

- Attractive design
- Low noise level
- Optimal air distribution in cooling & heating mode



Under ceiling unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series.

Elegant design with rounded edges and a large air control fin for optimal air circulation. Available in seven power levels from 4.5 to 16.0 kW.



Performance

- Very high energy efficiency
- Optimal temperature distribution right down to the floor in heating mode
- High-performance heat exchanger
- Self-cleaning function
- Low-noise, 3-stage fan
- Quiet function
- Auto diagnostic system



Technical details

- Easy installation via removable suspension fixtures
- TCB-DP31CE drain pump optionally available
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage



Flexibility

- Optimal air distribution, even in high spaces
- Easy-to-remove, washable dust filters
- Additional boards available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Ceiling unit

Technical data			MMC-AP0158HP-E
Cooling capacity	kW	❄️	4,50
Power consumption (min./nom./max.)	kW	❄️	0,033
Heating capacity	kW	🔥	5,00
Power consumption (min./nom./max.)	kW	🔥	0,033
Airflow	m ³ /h		540/690/840
Sound pressure level (low/med/high)	dB(A)	❄️	28/34/36
Sound pressure level (low/med/high)	dB(A)	🔥	28/34/36
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		12,7 (½)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1/50
Running current	A	❄️	0,36
Running current	A	🔥	0,36
Running current (nom.)	A		0,36
Current consumption (nom.)	A		0,36
Refrigerant			R410A
Dimensions (HxWxD)	mm		235 x 950 x 690
Weight	kg		24

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here: In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.

