



INDIVIDUAL COVERING

Chassis SMMSu



Highlights

- Easy installation
- For on-site covering
- Perfect for historic buildings, etc.



Chassis unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series. The unit integrates itself perfectly into the space while matching the interior thanks to an on-site covering. Available in six capacity sizes from 2.2 to 7.1 kW.



Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 5-stage fan
- Auto diagnostic system



Flexibility

- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Can be combined with all wired remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart after power blackout adjustable



Chassis SMMSu

Technical data			MML-UP0121BH-E
Cooling capacity	kW	❄️	3,60
Power consumption (min./nom./max.)	kW	❄️	0,056
Heating capacity	kW	🔥	4,00
Power consumption (min./nom./max.)	kW	🔥	0,056
Airflow	m ³ /h		300/400/460
Sound pressure level (low/med/high)	dB(A)	❄️	32/34/36
Sound pressure level (low/med/high)	dB(A)	🔥	32/34/36
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,25
Running current	A	🔥	0,25
Current consumption (nom.)	A		0,25
Refrigerant			R410A
Dimensions (HxWxD)	mm		600 x 745 x 220
Weight	kg		21

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Self-cleaning function: Usage of condensate water for cleaning.

