



## INDIVIDUAL COVERING

# Chassis SMMSu



### Highlights

- Easy installation
- For on-site covering
- Perfect for historic buildings, etc.



Chassis unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series. The unit integrates itself perfectly into the space while matching the interior thanks to an on-site covering. Available in six capacity sizes from 2.2 to 7.1 kW.



### Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 5-stage fan
- Auto diagnostic system



### Technical details

- Can be combined with all wired remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart after power blackout adjustable



### Flexibility

- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



## Chassis SMMSu

Technical data			MML-UP0151BH-E
Cooling capacity	kW	❄️	4,50
Power consumption (min./nom./max.)	kW	❄️	0,090
Heating capacity	kW	🔥	5,00
Power consumption (min./nom./max.)	kW	🔥	0,090
Airflow	m <sup>3</sup> /h		460/600/740
Sound pressure level (low/med/high)	dB(A)	❄️	32/34/36
Sound pressure level (low/med/high)	dB(A)	🔥	32/34/36
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		12,7 (½)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,45
Running current	A	🔥	0,45
Current consumption (nom.)	A		0,45
Refrigerant			R410A
Dimensions (HxWxD)	mm		600 x 1045 x 220
Weight	kg		29

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Self-cleaning function:** Usage of condensate water for cleaning.

