



SUITABLE FOR ANY ROOM

## Console unit SMMSu



### Highlights

- Individual choice of air flow direction
- Floor heating effect
- "Smart User Interface" for direct unit operation



Console unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u and SHRM-e model series. Smaller than a standard heater, but still with a flexible air outlet and the unique floor heating effect. Available in five capacity sizes from 2.2 to 5.6 kW.



### Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 5-step fan
- Auto diagnostic system



### Flexibility

- Two air outlets
- Optimal air distribution in heating mode
- Easy-to-remove, washable dust filters
- Optional Aktiv-Carbon-Katechin filter strips (Art. 818F0023)
- Optional IAQ filter strips (Art. 818F0036)
- Optional Ultra-Pure 2.5 filter strips (Art. 818F0050)



### Easy operation

- Infrared remote control included
- On/Off timer
- Automatic mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- Optional WiFi control via smartphone, tablet, or PC



### Technical details

- Can be combined with all wired remote controls
- Automatic restart after power blackout adjustable



## Console unit SMMSu

Technical data			MML-UP0071NHP-E
Cooling capacity	kW	❄️	2,20
Power consumption (min./nom./max.)	kW	❄️	0,021
Heating capacity	kW	🔥	2,50
Power consumption (min./nom./max.)	kW	🔥	0,021
Airflow	m <sup>3</sup> /h		282/366/510
Sound pressure level (low/med/high)	dB(A)	❄️	26/32/38
Sound pressure level (low/med/high)	dB(A)	🔥	26/32/38
Sound power level	dB(A)	❄️	41/47/53
Sound power level	dB(A)	🔥	41/47/53
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Condensate pipe diameter	mm		VP16
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,20
Running current	A	🔥	0,20
Current consumption (nom.)	A		0,20
Refrigerant			R410A
Dimensions (HxWxD)	mm		600 x 700 x 220
Weight	kg		17

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Self-cleaning function:** Usage of condensate water for cleaning.



**Auto diagnostic:** Check of system for flawless operation.



**Comfort Sleep:** Gradual increase of temperature by 2 °C until morning.



**Timer:** Individual programming of on-/off times.



**Dust filter:** Washable filter against coarse contamination.



**HI POWER:** Particularly strong airflow for quickly reaching the requested temperature.



**Quiet Mode:** Whisper mode for the indoor unit.



**Preset Mode:** Activates individual settings at the touch of a button.

