


SUITABLE FOR ANY ROOM

Console unit SMMSu



Highlights

- Individual choice of air flow direction
- Floor heating effect
- "Smart User Interface" for direct unit operation



Console unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u and SHRM-e model series. Smaller than a standard heater, but still with a flexible air outlet and the unique floor heating effect. Available in five capacity sizes from 2.2 to 5.6 kW.



Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 5-step fan
- Auto diagnostic system



Flexibility

- Two air outlets
- Optimal air distribution in heating mode
- Easy-to-remove, washable dust filters
- Optional Aktiv-Carbon-Katechin filter strips (Art. 818F0023)
- Optional IAQ filter strips (Art. 818F0036)
- Optional Ultra-Pure 2.5 filter strips (Art. 818F0050)



Easy operation

- Infrared remote control included
- On/Off timer
- Automatic mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Can be combined with all wired remote controls
- Automatic restart after power blackout adjustable



Console unit SMMSu

Technical data			MML-UP0181NHP-E
Cooling capacity	kW	❄️	5,60
Power consumption (min./nom./max.)	kW	❄️	0,052
Heating capacity	kW	🔥	6,30
Power consumption (min./nom./max.)	kW	🔥	0,052
Airflow	m ³ /h		426/528/726
Sound pressure level (low/med/high)	dB(A)	❄️	34/40/47
Sound pressure level (low/med/high)	dB(A)	🔥	34/40/47
Sound power level	dB(A)	❄️	49/55/62
Sound power level	dB(A)	🔥	49/55/62
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		12,7 (½)
Condensate pipe diameter	mm		VP16
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,43
Running current	A	🔥	0,43
Current consumption (nom.)	A		0,42
Refrigerant			R410A
Dimensions (HxWxD)	mm		600 x 700 x 220
Weight	kg		17

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Self-cleaning function: Usage of condensate water for cleaning.



Auto diagnostic: Check of system for flawless operation.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



Timer: Individual programming of on-/off times.



Dust filter: Washable filter against coarse contamination.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Quiet Mode: Whisper mode for the indoor unit.



Preset Mode: Activates individual settings at the touch of a button.

