PREMIUM SINGLE-SPLIT

Daiseikai 9 - R32





Maximum energy efficiency A+++
"Wooden texture reflect" finish in white
"Fireplace" operating mode
Two "silent" modes for the outdoor unit

Daiseikai 9 combines design with comfort and the ultimate in efficiency. Both outdoor and indoor units combine flawless operation with timeless design and the very best air filter system.



Attractive and economical

- Highest energy efficiency (A+++)
- SEER values up to 10.6
- Direct current hybrid inverter technology
- Twin-rotary compressor
- Exceptionally high efficiency in the partial load range
- Single installation
- Colored, dimmable LED displays
- Draft-free comfort due to 3D air distribution
- Stylish wooden texture reflect surface



Resource-friendly

- Inverter control minimizes electricity consumption
- Eco operation
- Air used as energy source in heating mode
- Unobtrusive design fits any interior
- Compact & quiet outdoor unit



Cleaner ambient air

- Washable dust filter that covers the entire heat exchanger
- Special coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Plasma filter
- SUPER ionizer
- Optional active carbon-catechin filter strips (art.818F0023)
- Optional IAQ filter strips (art.818F0036)

Easy operation

- Comes with comfort infrared remote control as standard
- Clear & easy operation
- Large, backlit display
- Weekly timer with 4 freely programmable settings per day
- 28 time programs per week
- 8°C frost protection function
- Power Select
- Automatic mode
- Eco mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- 3D airflow with 6 air flow patterns
- Automatic restart setting after power outage
- Cooling-only & heating-only settings
- Optional WiFi control via smartphone, tablet, or PC
- Fireplace operating mode uses heat from other sources
- Silent mode reduces outdoor unit sound pressure by up to 4 dB(A)



Daiseikai 9 - R32 / SET

Indoor unit			RAS-10PKVPG-E
Outdoor unit			RAS-10PAVPG-E
Cooling capacity	kW	*	2,50
Cooling range (minmax.)	kW	*	0,80 - 3,50
Power consumption (min./nom./max.)	kW	*	0,15/0,45/0,82
Pdesign c	kW		2,50
Energy efficiency EER	W/W	*	5,56
Energy efficiency SEER		*	10,60
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	83
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	3,20
Heating range (minmax.)	kW	*	0,70 - 5,80
Power consumption (min./nom./max.)	kW	*	0,15/0,60/1,55
Pdesign h	kW		3,00
Energy efficiency COP	W/W	*	5,33
Energy efficiency SCOP		*	5,20
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	807
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-10PKVPG-E
Sound pressure level (low/med/high)	dB(A)	*	20/33/44
Sound pressure level (low/med/high)	dB(A)	*	20/33/44
Sound power level	dB(A)	*	58
Sound power level	dB(A)	*	59
Airflow	m³/h		690
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		293 x 851 x 270
Weight	kg		14

* Cooling + Heating

Daiseikai 9 - R32 / SET

Outdoor unit			RAS-10PAVPG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		10
Current consumption (nom.)	А		3,12
Current consumption (max.)	А		2,86
Sound pressure level (low/med/high)	dB(A)	*	46
Sound pressure level (low/med/high)	dB(A)	*	47
Sound power level	dB(A)	*	61
Sound power level	dB(A)	*	62
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		25
Height difference (max.)	m		10
Airflow	m³/h		2160
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,00
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 800 x 300
Weight	kg		43

* Cooling Heating

The measuring conditions for this product can be found at http://www.toshiba-klima.at/en/measuring-conditions.html

TOSHIBA Features - general overview



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative iones cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.