

## VERSATILE WORKHORSE

### Digital Inverter series 3



#### Highlights

- compact – durable – efficient
- Easy-install features
- Easy commissioning functions
- 3-level silent setting

Digital-Inverter outdoor units for RAV single-room systems with refrigerant R32, for cooling- or heating operation with a wide performance spectrum. To be combined with RAV-HM indoor units or DX-kit. Available in nine capacity sizes from 2,5 to 14,0 kW cooling capacity and 3,4 to 16,0 kW heating capacity.



#### Performance

- Suitable for 24/7 continual operation
- Ideal for server rooms and humidity-sensitive applications
- Exceptionally high efficiency in part load range
- Controls at the lowest minimum capacities
- Small and lightweight chassis in 4 sizes
- Corresponds to the ECODESIGN Lot 10 Directive



#### Flexibility

- Max. pipe lengths up to 50 m
- Max. height differences up to 30 m
- Flexible control options available
- Wide operating temperature range



#### Technical details

- Twin rotary compressor
- Direct current hybrid inverter technology
- All units 1-phase, 230 V available
- Capacities 10, 12, 14 kW alternative 3-phase, 400V available
- Inspection window simplifies maintenance
- Kit available for noise reduction, max. capacity control, compressor operating signal
- 3-stage night operation adjustable
- Save Operation setting for demand limitation of 50% to 100%



#### The Digital Inverter system

- 100% TU2C-link compatibility
- DX kit available for connecting external heat exchangers
- Special solutions for Technical Cooling /IT
- Backup / rotation / redundancy functions
- Free Cooling Control ensures energy savings in technical cooling by utilizing outside air.
- Power Shift increases lifetime and saves energy
- Secondary Heating for controlling an additional heat source with only one remote control
- Supports new comfort remote control RBC-AMSU52-E
- Supports new comfort remote control RBC-AWSU52-E with Bluetooth functionality
- Optional WiFi control for comfort & security
- Energy monitoring via WiFi interface
- Step-by-step commissioning function
- Special Quick Service Tools
- Commissioning Mode for clear display of all sensor data
- LC Easy Monitor menu to check all sensor information
- Easy I.DN Setting for easy DN code setting
- Refrigerant amount check during test run
- Alternating defrosting for comfort & safety
- Self-test of indoor unit functions



## Digital Inverter series 3

| Technical data                                  |           |    | RAV-GM903ATP-E  |
|-------------------------------------------------|-----------|----|-----------------|
| Cooling capacity                                | kW        | ❄️ | 8,00            |
| Cooling range (min.-max.)                       | kW        | ❄️ | 1,90 - 8,80     |
| Energy efficiency class                         |           | ❄️ | A++             |
| Outdoor temperature operating range (min.-max.) | °C        | ❄️ | -20 / +46       |
| Heating capacity                                | kW        | 🔥  | 9,00            |
| Heating range (min.-max.)                       | kW        | 🔥  | 1,60 - 9,90     |
| Outdoor temperature operating range (min.-max.) | °C        | 🔥  | -20 / +15       |
| Sound power level                               | dB(A)     | ❄️ | 66              |
| Sound power level                               | dB(A)     | 🔥  | 66              |
| Sound pressure level (low/med/high)             | dB(A)     | ❄️ | 49              |
| Sound pressure level (low/med/high)             | dB(A)     | 🔥  | 50              |
| Suction gas pipe diameter                       | mm (inch) |    | 15,9 (5/8)      |
| Liquid pipe diameter                            | mm (inch) |    | 9,5 (3/8)       |
| Pipe length (min.)                              | m         |    | 5               |
| Pipe length (max.)                              | m         |    | 50              |
| Height difference (max.)                        | m         |    | 30              |
| Airflow                                         | m³/h      |    | 2580            |
| Power supply                                    | V/Ph+N/Hz |    | 220-240/1+N/50  |
| Compressor type                                 |           |    | Twin-Rotary     |
| Refrigerant                                     |           |    | R32             |
| Refrigerant charge                              | kg        |    | 2,00            |
| Pre-charged up to                               | m         |    | 20              |
| Added refrigerant charge                        | g/m       |    | 35              |
| Dimensions (HxWxD)                              | mm        |    | 630 x 800 x 300 |
| Weight                                          | kg        |    | 46              |
| SWL (LW) Night Operation, Level 1/2/3           | dB(A)     | ❄️ | 59/61/63        |
| SWL (LW) Night Operation, Level 1/2/3           | dB(A)     | 🔥  | 60/62/64        |
| SPL (Lp) Night Operation, Level 1/2/3           | dB(A)     | ❄️ | 44/46/48        |
| SPL (Lp) Night Operation, Level 1/2/3           | dB(A)     | 🔥  | 45/47/49        |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

