

SPACE-SAVING – FOR ANY ROOM

Floor standing unit SL R32



Highlights

- SL »speed line« feature update
- Perfect air circulation
- Floor installation - for the easiest installation
- Integrated leak detection system

Floor standing unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Provides optimum air circulation while taking up minimal installation space. Available in six capacity sizes from 5.0 to 14.0 kW.



Performance

- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution, even in large spaces
- Easy-to-remove, washable dust filters
- Additional TCB-PCUC2E board available for external analog & digital control



Technical Details

- Integrated leak detection system simplifies EN378 conformance
- Can be combined with all wired remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart after power blackout
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



Floor standing unit SL R32 / SET

Indoor unit			RAV-HM901FT-E
Outdoor unit			RAV-GM903ATP-E
Cooling capacity	kW	❄️	8,00
Cooling range (min.-max.)	kW	❄️	1,90 - 8,80
Power consumption (min./nom./max.)	kW	❄️	- / 2,43 / -
Energy efficiency EER	W/W	❄️	3,30
Energy efficiency SEER		❄️	6,24
Energy efficiency class		❄️	A++
Outdoor temperature operating range (min.-max.)	°C	❄️	-20 / +46
Heating capacity	kW	🔥	9,00
Heating range (min.-max.)	kW	🔥	1,60 - 9,90
Power consumption (min./nom./max.)	kW	🔥	- / 2,43 / -
Energy efficiency COP	W/W	🔥	3,70
Energy efficiency SCOP		🔥	4,00
Energy efficiency class		🔥	A+
Outdoor temperature operating range (min.-max.)	°C	🔥	-20 / +15

Indoor unit			RAV-HM901FT-E
Sound pressure level (low/med/high)	dB(A)	❄️	37/40/45
Sound pressure level (low/med/high)	dB(A)	🔥	37/40/45
Sound power level	dB(A)	❄️	51/54/59
Sound power level	dB(A)	🔥	51/54/59
Airflow	m³/h		820/1070/1330
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		1750 x 600 x 390
Weight	kg		59

❄️ Cooling 🔥 Heating



Floor standing unit SL R32 / SET

Outdoor unit			RAV-GM903ATP-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		16
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Running current	A	❄️	10,40 - 11,35
Running current	A	🔥	10,45 - 11,40
Current consumption (nom.)	A		16,62
Current consumption (max.)	A		16,62
Sound power level	dB(A)	❄️	66
Sound power level	dB(A)	🔥	66
Sound pressure level (low/med/high)	dB(A)	❄️	49
Sound pressure level (low/med/high)	dB(A)	🔥	50
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m³/h		2580
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		2,00
Pre-charged up to	m		20
Added refrigerant charge	g/m		35
Dimensions (HxWxD)	mm		630 x 800 x 300
Weight	kg		46

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

