

SPACE-SAVING – FOR ANY ROOM

## Floor unit SMMSu



### Highlights

- Free positioning
- "Auto swing" for louver
- Front recess for installation of a remote control



Floor unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u and SHRM-e model series. Best possible air distribution due to louver swing mode – even when placed in the corner of a room. Available in seven capacity sizes from 4.5 to 16.0 kW.



### Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 3-stage fan
- Auto diagnostic system



### Technical details

- Can be combined with all wired remote controls
- External receiver kit for infrared remote control possible
- Automatic restart after power blackout adjustable



### Flexibility

- Wide air outlet
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



## Floor unit SMMSu

Technical data			MMF-UP0561H-E
Cooling capacity	kW	❄️	16,00
Power consumption (min./nom./max.)	kW	❄️	0,160
Heating capacity	kW	🔥	18,00
Power consumption (min./nom./max.)	kW	🔥	0,160
Airflow	m <sup>3</sup> /h		1560/1730/2160
Sound pressure level (low/med/high)	dB(A)	❄️	44/49/54
Sound pressure level (low/med/high)	dB(A)	🔥	44/49/54
Sound power level	dB(A)	❄️	62/67/72
Sound power level	dB(A)	🔥	62/67/72
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	1,10
Running current	A	🔥	1,10
Current consumption (nom.)	A		1,10
Refrigerant			R410A
Dimensions (HxWxD)	mm		1750 x 600 x 390
Weight	kg		62

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Dust filter:** Washable filter against coarse contamination.



**Self-cleaning function:** Usage of condensate water for cleaning.

