

SPACE-SAVING – FOR ANY ROOM

Floor unit SMMSu



Highlights

- Free positioning
- "Auto swing" for louver
- Front recess for installation of a remote control



Floor unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u and SHRM-e model series. Best possible air distribution due to louver swing mode – even when placed in the corner of a room. Available in seven capacity sizes from 4.5 to 16.0 kW.



Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 3-stage fan
- Auto diagnostic system



Technical details

- Can be combined with all wired remote controls
- External receiver kit for infrared remote control possible
- Automatic restart after power blackout adjustable



Flexibility

- Wide air outlet
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Floor unit SMMSu

| Technical data | | | MMF-UP0241H-E |
|-------------------------------------|-------------------|----|------------------|
| Cooling capacity | kW | ❄️ | 7,10 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,089 |
| Heating capacity | kW | 🔥 | 8,00 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,089 |
| Airflow | m ³ /h | | 840/990/1200 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 39/45/49 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 39/45/49 |
| Sound power level | dB(A) | ❄️ | 57/63/67 |
| Sound power level | dB(A) | 🔥 | 57/63/67 |
| Liquid pipe diameter | mm (inch) | | 9,5 (3/8) |
| Suction gas pipe diameter | mm (inch) | | 15,9 (5/8) |
| Condensate pipe diameter | mm | | VP20 (20/26) |
| Power supply | V/Ph+N/Hz | | 220-240/1+N/50 |
| Running current | A | ❄️ | 0,60 |
| Running current | A | 🔥 | 0,60 |
| Current consumption (nom.) | A | | 0,60 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 1750 x 600 x 210 |
| Weight | kg | | 47 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.

