TOSHIBA

SPACE-SAVING - FOR ANY ROOM

Floor unit SMMSu



Highlights

Free positioning
"Auto swing" for louver
Front recess for installation of a
remote control







Floor unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u and SHRM-e model series. Best possible air distribution due to louver swing mode – even when placed in the corner of a room. Available in seven capacity sizes from 4.5 to 16.0 kW.



Performance

- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise, 3-stage fan
- _ Auto diagnostic system



Flexibility

- _ Wide air outlet
- Easy-to-remove, washable dust filter
- $_{\rm -}\,$ Optional WiFi control via smartphone, tablet, or PC



Technical details

- Can be combined with all wired remote controls
- External receiver kit for infrared remote control possible
- Automatic restart after power blackout adjustable



TOSHIBA

Floor unit SMMSu

Technical data			MMF-UP0271H-E
Cooling capacity	kW	*	8,00
Power consumption (min./nom./max.)	kW	*	0,089
Heating capacity	kW	*	9,00
Power consumption (min./nom./max.)	kW	*	0,089
Airflow	m³/h		840/990/1200
Sound pressure level (low/med/high)	dB(A)	*	39/45/49
Sound pressure level (low/med/high)	dB(A)	*	39/45/49
Sound power level	dB(A)	*	57/63/67
Sound power level	dB(A)	*	57/63/67
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Condensate pipe diameter	mm		VP20 (20/26)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	А	*	0,60
Running current	А	*	0,60
Current consumption (nom.)	А		0,60
Refrigerant			R410A
Dimensions (HxWxD)	mm		1750 x 600 x 210
Weight	kg		47

Reating Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html



TOSHIBA

In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.

