



## COMFORT ALLROUNDER

### High-wall unit SL R32



#### Highlights

- SL »speed line« feature update
- Modern, compact design
- Comfort features taken from HOME sector
- Preset, Quiet, Hi Power, Comfort Sleep
- Infrared remote control included

High-wall unit for RAV single-room systems for combination with Digital-Inverter CLASSIC, Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. With their unobtrusive design, these high-wall units are ideal for offices, shops, hotels, technical cooling, restaurants, etc. Available in six capacity sizes from 2.5 to 10.0 kW.



#### Performance

- Suitable for 24-hour continuous operation
- High energy efficiency
- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise 5-stage fan
- Auto diagnostic system



#### Flexibility

- Optimal air distribution, even in large spaces
- Easy-to-remove, washable dust filters
- "Easy Cleaning" design
- Optional WiFi control via smartphone, tablet, or PC



#### Easy operation

- Infrared remote control included
- 24-hour timer
- Automatic mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep



#### Technical details

- Can be combined with all cable remote controls
- Integrated TCC / TU2C link interface
- Can be integrated into VRF control systems via link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available
- Refrigerant lines can be connected from 3 sides



#### SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



## High-wall unit SL R32 / SET

Indoor unit			RAV-HM301KRTP-E
Outdoor unit			RAV-GM302ATP-E
Cooling capacity	kW	❄️	2,50
Cooling range (min.-max.)	kW	❄️	0,90 - 3,00
Power consumption (min./nom./max.)	kW	❄️	0,25/0,61/0,82
Energy efficiency EER	W/W	❄️	4,10
Energy efficiency SEER		❄️	6,36
Energy efficiency class		❄️	A++
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +46
Heating capacity	kW	🔥	3,40
Heating range (min.-max.)	kW	🔥	0,80 - 4,50
Power consumption (min./nom./max.)	kW	🔥	0,17/0,85/1,40
Energy efficiency COP	W/W	🔥	4,00
Energy efficiency SCOP		🔥	4,10
Energy efficiency class		🔥	A+
Outdoor temperature operating range (min.-max.)	°C	🔥	-15 / +15

Indoor unit			RAV-HM301KRTP-E
Sound pressure level (low/med/high)	dB(A)	❄️	29/34/40
Sound pressure level (low/med/high)	dB(A)	🔥	29/34/40
Sound power level	dB(A)	❄️	44/49/55
Sound power level	dB(A)	🔥	44/49/55
Airflow	m³/h		450/540/670
Condensate pipe diameter	mm		VP16
Dimensions (HxWxD)	mm		293 x 798 x 230
Weight	kg		10

❄️ Cooling 🔥 Heating



## High-wall unit SL R32 / SET

Outdoor unit			RAV-GM302ATP-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		10
Running current	A	❄️	2,83 - 3,07
Running current	A	🔥	3,80 - 4,17
Current consumption (nom.)	A		2,83
Current consumption (max.)	A		7,9
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	47
Sound power level	dB(A)	❄️	61
Sound power level	dB(A)	🔥	62
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		10
Airflow	m³/h		1800
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		0,6
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		29

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

