



COMPACT ALLROUNDER

High-wall unit series 1 SMMSu



Highlights

- Space-saving & compact
- Optimum air distribution through large louver flap
- Extremely quiet external PMV version available (sizes 003 to 024)



Compact high-wall unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series (size 003 for SMMS-u only). With their unobtrusive design, these high-wall units fit in offices, shops, hotels, utility rooms, restaurants, etc. Available in eleven capacity sizes from 0.7 to 11.2 kW.



Performance

- Modern, slim design
- Colorful, dimmable LED indicators
- Self-cleaning function dries the heat exchanger after operation has ended
- Quiet 5-stage fan
- Auto diagnostic system



Flexibility

- Large air fin
- Optimal air distribution, even in large spaces
- Washable dust filter that is easy to remove
- Cleaner ambient air
- Washable dust filter that covers the entire heat exchanger
- "Dustless coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation has ended
- Optional Aktiv-Carbon-Katechin filter strips (Art. 818F0023)
- Optional IAQ filter strips (Art. 818F0036)
- Optional Ultra-Pure 2.5 filter strips (Art. 818F0050)



Easy operation

- Comes with infrared remote controls
- On/off timer
- Automatic mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Can be combined with all wired remote controls
- Automatic restart after power blackout adjustable
- Refrigerant piping can be connected from three sides



High-wall unit series 1 SMMSu

| Technical data | | | MMK-UP0051HP-E |
|-------------------------------------|-------------------|----|-----------------|
| Cooling capacity | kW | ❄️ | 1,70 |
| Power consumption (min./nom./max.) | kW | ❄️ | 0,013 |
| Heating capacity | kW | 🔥 | 1,90 |
| Power consumption (min./nom./max.) | kW | 🔥 | 0,013 |
| Airflow | m ³ /h | | 270/370/455 |
| Sound pressure level (low/med/high) | dB(A) | ❄️ | 25/29/33 |
| Sound pressure level (low/med/high) | dB(A) | 🔥 | 25/29/33 |
| Liquid pipe diameter | mm (inch) | | 6,4 (¼) |
| Suction gas pipe diameter | mm (inch) | | 9,5 (3/8) |
| Condensate pipe diameter | mm | | VP16 |
| Power supply | V/Ph+N/Hz | | 220-240/1+N/50 |
| Running current | A | ❄️ | 0,15 |
| Running current | A | 🔥 | 0,15 |
| Current consumption (nom.) | A | | 0,15 |
| Refrigerant | | | R410A |
| Dimensions (HxWxD) | mm | | 293 x 798 x 230 |
| Weight | kg | | 11,0 |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Self-cleaning function: Usage of condensate water for cleaning.



Quiet Mode: Whisper mode for the indoor unit.



Dust filter: Washable filter against coarse contamination.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.

