



## COMPACT ALLROUNDER

### High-wall unit series 1 SMMSu



#### Highlights

- Space-saving & compact
- Optimum air distribution through large louver flap
- Extremely quiet external PMV version available (sizes 003 to 024)

Compact high-wall unit for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, SMMS-u, and SHRM-e model series (size 003 for SMMS-u only). With their unobtrusive design, these high-wall units fit in offices, shops, hotels, utility rooms, restaurants, etc. Available in eleven capacity sizes from 0.7 to 11.2 kW.



#### Performance

- Modern, slim design
- Colorful, dimmable LED indicators
- Self-cleaning function dries the heat exchanger after operation has ended
- Quiet 5-stage fan
- Auto diagnostic system



#### Flexibility

- Large air fin
- Optimal air distribution, even in large spaces
- Washable dust filter that is easy to remove
- Cleaner ambient air
- Washable dust filter that covers the entire heat exchanger
- "Dustless coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation has ended
- Optional Aktiv-Carbon-Katechin filter strips (Art. 818F0023)
- Optional IAQ filter strips (Art. 818F0036)
- Optional Ultra-Pure 2.5 filter strips (Art. 818F0050)



#### Easy operation

- Comes with infrared remote controls
- On/off timer
- Automatic mode
- Hi Power
- Quiet
- Preset
- Comfort Sleep
- Optional WiFi control via smartphone, tablet, or PC



#### Technical details

- Can be combined with all wired remote controls
- Automatic restart after power blackout adjustable
- Refrigerant piping can be connected from three sides



## High-wall unit series 1 SMMSu

Technical data			MMK-UP0301HP-E
Cooling capacity	kW	❄️	9,00
Power consumption (min./nom./max.)	kW	❄️	0,054
Heating capacity	kW	🔥	10,00
Power consumption (min./nom./max.)	kW	🔥	0,054
Airflow	m <sup>3</sup> /h		1100/1300/1500
Sound pressure level (low/med/high)	dB(A)	❄️	41/44/48
Sound pressure level (low/med/high)	dB(A)	🔥	41/44/48
Sound power level	dB(A)	❄️	56/59/63
Sound power level	dB(A)	🔥	56/59/63
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,8 (5/8)
Condensate pipe diameter	mm		16
Power supply	V/Ph+N/Hz		220-240/1+N/50
Running current	A	❄️	0,46
Running current	A	🔥	0,46
Refrigerant			R410A
Dimensions (HxWxD)	mm		350 x 1200 x 280
Weight	kg		21

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

