




2-pipe in compact format

MiNi SMMS R32

→ Highlights

Ultra-compact VRF outdoor unit for up to 13 indoor units
For 2-pipe systems up to 15.5 kW cooling & heating
Optimum environmental protection: Made in Europe - Low GWP refrigerant - night operation
Comprehensive and simple safety concept



Compact VRF 2-pipe outdoor unit for cooling or heating operation with a wide performance spectrum. For combination with VRF indoor units, according to Selection-Tool design software.

→ Performance

- SEER values up to 9.98
- SCOP values up to 5.21
- Optimized R32 refrigeration circuit enables lowest refrigerant quantities
- Outstanding energy and cost efficiency
- Suitable for monovalent heating operation
- Heat exchanger defrosting in heating mode without loss of comfort

→ Flexibility

- Maximum piping lengths of up to 300 m
- Maximum height differences up to 50 m
- Up to 13 indoor units can be connected
- Flexible control options for all applications
- Night Operation: Quiet operation protects people and the environment
- System diversity up to 130%
- Simple system design with Selection-Tool software

→ Safety

- Safety concept in accordance with IEC 60335-2-40 (Ed.6)
- Simple application according to design recommendation

→ Technical details

- Perfected A2 twin-rotary compressor
- Double-vane technology with carbon coating
- Continuous heating operation for up to 5 hours
- Ultra-short defrosting cycles of up to 3.5 minutes
- Intelligent refrigerant management ensures optimum supply to all indoor units, regardless of their position in the building
- Shortest oil recovery cycles thanks to intelligent oil management algorithms
- Fast TU2C-Link system bus with 19,200 bps
- The wireless NFC Wave Tool function simplifies commissioning, service and system monitoring with Android and iOS smartphones
- The DynaDoctor service tool for convenient recording, monitoring and diagnostics as a PC application can be connected to outdoor or indoor units via USB
- Optional TCB-SS1UU-E Service Link Adapter enables data logging to micro SDHC card (included, 8 GB) even without a PC



Mini SMMS R32

Technical data			MCY-MUG0501HSW-E
Capacity code	HP		5
Cooling capacity	kW	❄️	14,00
Power consumption (min./nom./max.)	kW	❄️	3,73
Energy efficiency EER	W/W	❄️	3,75
Energy efficiency SEER		❄️	9,21
Energy efficiency ETAs	%	❄️	365,4
Running current	A	❄️	16,3
Heating capacity	kW	🔥	14,00
Power consumption (min./nom./max.)	kW	🔥	2,95
Energy efficiency COP	W/W	🔥	4,75
Energy efficiency SCOP		🔥	4,93
Energy efficiency ETAs	%	🔥	194,2
Running current	A	🔥	13,2
Airflow	m³/h		4740
External static pressure	Pa		20
Sound pressure level (low/med/high)	dB(A)	❄️	53
Sound pressure level (low/med/high)	dB(A)	🔥	55
Sound power level	dB(A)	❄️	70
Sound power level	dB(A)	🔥	72
Sound pressure level (night operation, @ 1m)	dB(A)	❄️	50/47/44
Compressor type			Twin-Rotary
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,8 (5/8)
Outdoor temperature operating range (min.-max.)	°C	❄️	-5 / +46
Outdoor temperature operating range (min.-max.)	°C	🔥	-20 / +15
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		32
Recommended power supply line type			H07RN-F 3G4,0
Communication line			YSLCY 2x1,5
Current consumption (nom.)	A		13,20/16,30
Current consumption (max.)	A		26,50
Connectable indoor units (max.)	Pce.		10
Pipe length (max.)	m		300
Height difference (max.)	m		40/50
Refrigerant			R32
Refrigerant charge	kg		2,40
Dimensions (HxWxD)	mm		1050 x 1010 x 370
Weight	kg		100

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Hybrid inverter control: Smooth capacity regulation.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R32: Used refrigerant: R32.

