TOSHIBA




2-pipe in compact format

MiNi SMMS R32

Highlights

Ultra-compact VRF outdoor unit for up to 18 indoor units
For 2-pipe systems up to 15.5 kW cooling & heating
Comprehensive and simple safety concept



Compact VRF 2-pipe outdoor unit for cooling or heating operation with a wide performance spectrum. For combination with VRF indoor units, according to Selection-Tool design software.Available for 1-phase, 230V or 3-phase, 400V power supply.

Performance

- SEER values up to 10.00
- SCOP values up to 5.36
- Optimized R32 refrigeration circuit enables lowest refrigerant quantities
- Suitable for monovalent heating operation
- Heat exchanger defrosting in heating mode without loss of comfort

Flexibility

- Maximum piping lenghts of up to 300 m
- Maximum height differences up to 50 m
- Up to 18 indoor units can be connected
- 230V and 400V versions available
- Flexible control options for all applications
- Night Operation: Quiet operation protects people and the environment
- System diversity 50% to 130%
- Simple system design with Selection-Tool software

Safety

- Safety concept in accordance with IEC 60335-2-40 (Ed.6)
- Simple application according to design recommendation

Technical details

- Perfected A2 twin-rotary compressor
- Double-vane technology with carbon coating
- Continuous heating operation for up to 5 hours
- Ultra-short defrosting cycles of up to 3.5 minutes
- Intelligent refrigerant management ensures optimum supply to all indoor units, regardless of their position in the building
- Shortest oil recovery cycles thanks to intelligent oil management algorithms
- Fast TU2C-Link system bus with 19,200 bps
- The DynaDoctor service tool for convenient recording, monitoring and diagnostics as a PC application can be connected to outdoor or indoor units via USB
- Optional TCB-SS1UU-E Service Link Adapter enables data logging to micro SDHC card (included, 8 GB) even without a PC

HIGHER quality in LIFE

TOSHIBA

MiNi SMMS R32

Technical data			MCY-MUG0602HSP-E
Capacity code	HP		4
Cooling capacity	kW	❄	15,50
Power consumption (min./nom./max.)	kW	❄	4,29
Energy efficiency EER	W/W	❄	3,61
Energy efficiency SEER		❄	8,80
Energy efficiency ETAs	%	❄	349,0
Running current	A	❄	18,6
Heating capacity	kW	☀	15,50
Power consumption (min./nom./max.)	kW	☀	3,36
Energy efficiency COP	W/W	☀	4,61
Energy efficiency SCOP		☀	4,80
Energy efficiency ETAs	%	☀	189,0
Running current	A	☀	14,8
Airflow	m^3/h		4740
External static pressure	Pa		20
Sound pressure level (low/med/high)	dB(A)	❄	54
Sound pressure level (low/med/high)	dB(A)	☀	56
Sound power level	dB(A)	❄	71
Sound power level	dB(A)	☀	73
Sound pressure level (night operation, @ 1m)	dB(A)	❄	50/47/44
Compressor type			Twin-Rotary
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		15,8 (5/8)
Outdoor temperature operating range (min.-max.)	°C	❄	-5 / +46
Outdoor temperature operating range (min.-max.)	°C	☀	-20 / +15
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		32
Recommended power supply line type			H07RN-F 3G4,0
Communication line			YSLCY 2x1,5
Current consumption (nom.)	A		14,80/18,60
Current consumption (max.)	A		28,50
Connectable indoor units (max.)	Pce.		13
Pipe length (max.)	m		300
Height difference (max.)	m		40/50
Refrigerant			R32
Refrigerant charge	kg		2,40
Dimensions (HxWxD)	mm		1050 x 1010 x 370
Weight	kg		100

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

HIGHER quality in LIFE

In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Hybrid inverter control: Smooth capacity regulation.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R32: Used refrigerant: R32.

HIGHER quality in LIFE