TOSHIBA




2-pipe in compact form

MiNi SMMSe

Highlights

Compact units, up to 33.5 kW of cooling-/heating capacity
Up to 16 indoor units can be connected



Compact VRF 2-pipe outdoor unit for cooling or heating with a wide performance spectrum. For combination with VRF indoor units.

Performance

- Suitable for monovalent heating operation
- Optional PMV kits can be used for noise-sensitive applications

Flexibility

- Max. pipe lengths up to 300 m
- Max. height differences up to 50 m
- Up to 16 indoor units can be connected (size 10, 12)
- Flexible control options for all applications
- Optimal ratio of unit capacity to installation surface
- Quiet operation protects people and the environment
- System diversity 80% to 130%
- Simple system design with SelectionTool-software

Technical details

- Inverter-controlled twin-rotary compressor
- Advanced fan design enables maximum capacity with minimum noise generation and current consumption
- Intelligent refrigerant management ensures an optimal supply to all indoor units, regardless of their position in the building

HIGHER quality in LIFE

TOSHIBA

MiNi SMMSe

Technical data			MCY-MHP1206HS8-E
Capacity code	HP		12
Cooling capacity	kW	❄	33,50
Power consumption (min./nom./max.)	kW	❄	12,18
Energy efficiency EER	W/W	❄	2,75
Energy efficiency SEER		❄	6,70
Running current	A	❄	18,70
Heating capacity	kW	☀	33,50
Power consumption (min./nom./max.)	kW	☀	7,94
Energy efficiency COP	W/W	☀	4,22
Energy efficiency SCOP		☀	4,30
Running current	A	☀	12,50
Airflow	m^3/h		9590
External static pressure	Pa		20
Sound pressure level (low/med/high)	dB(A)	❄	62
Sound pressure level (low/med/high)	dB(A)	☀	62
Sound power level	dB(A)	❄	76
Sound power level	dB(A)	☀	77
Sound pressure level (night operation, @ 1m)	dB(A)	❄	50
Compressor type			Twin-Rotary
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Suction gas pipe diameter	mm (inch)		22,2 (7/8)
Outdoor temperature operating range (min.-max.)	°C	❄	-15 / +46
Outdoor temperature operating range (min.-max.)	°C	☀	-20 / +15
Power supply	V/Ph+N/Hz		380-415/3+N/50
Recommended fusing	A		3x 25
Recommended power supply line type			H07RN-F 5G2,5
Communication line			YSLCY 2x1,5
Current consumption (nom.)	A		12,5
Current consumption (max.)	A		3x 23
Connectable indoor units (max.)	Pce.		16
Pipe length (max.)	m		250
Height difference (max.)	m		50
Refrigerant			R410A
Refrigerant charge	kg		4,40
Dimensions (HxWxD)	mm		1740 x 990 x 390
Weight	kg		156

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

HIGHER quality in LIFE

In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



Hybrid inverter control: Smooth capacity regulation.



R410A: Used refrigerant: R410A.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.

HIGHER quality in LIFE