


1:1 SINGLE-SPLIT OUTDOOR UNIT R32

## SHORAI

### → Highlights

- Can be connected to one indoor unit
- Piping lengths up to max. 25 m
- Compact, quiet & durable



Compact and quiet outdoor units with low-GWP refrigerant R32 for 1:1 combination with SHORAI EDGE or CONSOLES indoor units. In a robust, weatherproof housing, can be set up flexibly.

### → Economical & reliable

- Very high energy efficiency (A+++)
- DC hybrid inverter technology
- Single (07 to 16) or twin rotary compressor (18 to 24)
- Particularly high efficiency in part load range
- Complies with the ECODESIGN Lot10 guideline
- Wide operating temperature range
- Housing made of galvanized sheet steel with a cream-colored stove enamel finish
- Large curved heat exchanger for a small footprint
- Automatic restart after power failure adjustable

### → Saving resources

- Inverter control minimizes power consumption
- Eco mode
- Environmentally friendly low-GWP refrigerant R32 pre-filled
- Air as an energy source in heating mode
- Inconspicuous design adapts to any environment
- SILENT whisper mode

### → Comfort and economy functions

- Operation via comfort IR remote control (included with the indoor unit)
- Clear & simple operation
- Automatic mode
- Hi power
- Comfort sleep
- Weekly timer with 4 freely programmable settings / day
- 28 time programs per week
- SILENT operating mode
- 8 °C frost protection function
- Power Select
- Optional APP control via smartphone and tablet



## SHORAI / SET

Indoor unit	RAS-B16N4KVRG-E		
Outdoor unit	RAS-16J2AVSG-E1		
Cooling capacity	kW	❄️	4,60
Cooling range (min.-max.)	kW	❄️	1,20 - 5,30
Power consumption (min./nom./max.)	kW	❄️	0,34/1,35/1,72
Pdesign c	kW		4,6
Energy efficiency EER	W/W	❄️	3,41
Energy efficiency SEER		❄️	7,80
Energy efficiency class		❄️	A++
Annual electricity consumption	kWh/a	❄️	206
Outdoor temperature operating range (min.-max.)	°C	❄️	-15/+46
Heating capacity	kW	🔥	5,50
Heating range (min.-max.)	kW	🔥	1,10 - 6,30
Power consumption (min./nom./max.)	kW	🔥	0,30/1,52/1,90
Pdesign h	kW		4,0
Energy efficiency COP	W/W	🔥	3,62
Energy efficiency SCOP		🔥	4,60
Energy efficiency class		🔥	A++
Annual electricity consumption	kWh/a	🔥	1214
Outdoor temperature operating range (min.-max.)	°C	🔥	-15/+24

Indoor unit	RAS-B16N4KVRG-E		
Sound pressure level (low/med/high)	dB(A)	❄️	21/-/45
Sound pressure level (low/med/high)	dB(A)	🔥	22/-/45
Sound power level	dB(A)	❄️	58
Sound power level	dB(A)	🔥	58
Airflow	m <sup>3</sup> /h		340-730
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		300 x 987 x 210
Weight	kg		12

❄️ Cooling 🔥 Heating



## SHORAI / SET

Outdoor unit	RAS-16J2AVSG-E1		
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		10
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	A		5,61
Current consumption (max.)	A		9,50
Sound pressure level (low/med/high)	dB(A)	❄️	48
Sound pressure level (low/med/high)	dB(A)	🔥	50
Sound power level	dB(A)	❄️	61
Sound power level	dB(A)	🔥	63
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m <sup>3</sup> /h		2040
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,80
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		33

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

Accessories	Description
Fernbedienung	Infrared remote control included
RB-I4101-E	Fabric cover Dark Gray enclosed
RB-I4102-E	Fabric cover Light Gray enclosed
RB-I4103-E	Fabric cover Bluish Gray
RB-I4104-E	Fabric cover Gray Beige
RB-I4105-E	Fabric cover Dark Brown
RB-I4106-E	Fabric cover Emerald Blue
818F0023	Active carbon-catechin filter strips
818F0050	Ultra-pure 2.5 filter strips
TCB-IFCB5-PE	External on/off PCB, window contact module
TCB-PX100-PE	Casing for outdoor installation of window contact module for high-wall units



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**Energy Label A+++:** Energy efficiency class A+++ guarantees the lowest power consumption and the highest efficiency!



**Hybrid inverter control:** Smooth capacity regulation.



**Rotary compressor:** Reliability and high efficiency.



**R32:** Used refrigerant: R32.



**Auto diagnostic:** Check of system for flawless operation.

