
TOSHIBA



UNIVERSAL ALLROUNDER

SHORAI CURVE WHITE

Highlights

A +++ for cooling & heating
Plasma Ionizer air purification system
Careflow air distribution
WIFI adaptor integrated as standard
Lockable SILENT function

HIGH line hiwall unit in a classic WHITE matt design. Highest energy efficiency in combination with Ionizer air purifier and design remote control. 3D- and Careflow- air distribution move the air flow draft-free in the room. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2 to 5 room multi outdoor unit.

Attractive and economical

- Very high energy efficiency (A +++)
- DC Hybrid inverter technology
- Particularly high efficiency in part load range
- Reliable heating operation down to -20°C
- Whisper mode for indoor & outdoor units
- Colored, dimmable LED displays
- Draft-free comfort: 3D Airflow
- Intelligent airflow: Hada Careflow
- Horizontal and vertical louver adjustment lockable via the app
- The lockable SILENT function facilitates submissions to authorities and installation

Resource-friendly

- Inverter control minimizes power consumption
- ECO mode
- Air as an energy source in heating mode

Clean ambient air

- Washable dust filters
- MAGIC COIL coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after the end of operation
- Highly effective air purification with ionizer technology

Operation & features

- Design infrared remote control included (without holder #43T66468)
- Clear & simple operation
- Automatic mode, Hi power
- ON/OFF-timer (1 to 12 hours)
- Weekly timer with up to 6 programs/day
- QUIET mode for indoor unit
- The installer can lock the SILENT function of the outdoor unit
- Activation of Max/Min temperature settings by the installer
- Intelligent Defrost System, configurable via remote control and app
- 8 ° C frost protection function
- Fireplace mode
- Power Select
- Automatic restart after power failure adjustable
- APP control via smartphone and tablet
- WIFI module integrated in the indoor unit as standard
- An indoor unit can be operated by up to 5 users
- Up to 16 indoor units can be controlled by one user
- Several units can be combined in up to 3 groups / zones
- Child lock
- Multi-Language APP: German, English, Czech, Croatian, Hungarian, Slovenian, Slovak
- ENERGY MONITORING makes the power consumption transparent.

HIGHER quality in LIFE

TOSHIBA

SHORAI CURVE WHITE / SET

Indoor unit Outdoor unit			RAS-B13P2KVSG-E RAS-13P2AVSG-E
Cooling capacity	kW	❄	3,50
Cooling range (min.-max.)	kW	❄	1,00 - 4,10
Power consumption (min./nom./max.)	kW	❄	0,25/0,86/1,12
Energy efficiency EER	W/W	❄	4,07
Energy efficiency SEER		❄	8,60
Energy efficiency class		❄	A+++
Annual electricity consumption	kWh/a	❄	142
Outdoor temperature operating range (min.-max.)	°C	❄	-15/+46
Heating capacity	kW	☀	4,20
Heating range (min.-max.)	kW	☀	1,00 - 5,30
Power consumption (min./nom./max.)	kW	☀	0,20/1,08/1,55
Pdesign h	kW		3,20
Energy efficiency COP	W/W	☀	3,89
Energy efficiency SCOP		☀	5,10
Energy efficiency class		☀	A+++
Annual electricity consumption	kWh/a	☀	878
Outdoor temperature operating range (min.-max.)	°C	☀	-20/+24

Indoor unit			RAS-B13P2KVSG-E
Sound pressure level (low/med/high)	dB(A)	❄	19/--/43
Sound pressure level (low/med/high)	dB(A)	☀	19/--/43
Sound power level	dB(A)	❄	56
Sound power level	dB(A)	☀	56
Airflow	m^3/h		340-730
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		293 x 822 x 226
Weight	kg		10

❄ Cooling ☀ Heating

HIGHER quality in LIFE

TOSHIBA

SHORAI CURVE WHITE / SET

Outdoor unit			RAS-13P2AVSG-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		10
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	A		8,00
Current consumption (max.)	A		8,00
Sound power level	dB(A)	❄	60
Sound power level	dB(A)	☀	62
Sound pressure level (low/med/high)	dB(A)	❄	39/--/47
Sound pressure level (low/med/high)	dB(A)	☀	41/--/49
SWL (LW) Silent CDU #2	dB(A)	❄	52
SWL (LW) Silent CDU #2	dB(A)	☀	54
SPL (Lp) Silent CDU #2	dB(A)	❄	39
SPL (Lp) Silent CDU #2	dB(A)	☀	41
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
Liquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m^3/h		1950
Compressor type			DC Rotary
Refrigerant			R32
Refrigerant charge	kg		0,80
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		30

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

Accessories	Description
Fernbedienung	Infrared remote control included

HIGHER quality in LIFE