TOSHIBA



Heating and cooling simultaneously

SHRMu

Highlights

Maximum efficiency through heat recovery
Combinations up to 168 kW cooling and heating capacity
Robust twin or triple rotary compressors

VRF 3-pipe outdoor unit for simultaneous cooling and heating operation with a wide capacity range. For combination with VRF indoor units, DX-kits, and HRV heat exchangers. Uses refrigerant R410A.

Performance

- SEER efficiency values [illegible]up to 8.02
- Cooling efficiency Eta s ([illegible] up to 317 %
- SCOP efficiency values [illegible]up to 4.67
- Heating efficiency Eta s ([illegible] up to 183.8 %
- Suitable for monovalent heating operation

Flexibility

- Wide outdoor temperature operating range from -25 °C to +52 °C
- Maximum piping lengths up to 1,200 m
- Maximum height difference up to 90 m
- Up to 54 indoor units can be connected (single unit)
- Capacities up to 24 HP (64.5 kW) available with only one outdoor unit
- Fast TU2C-Link system bus
- Flexible control options for all applications
- Optimal ratio of unit output to installation area
- Quiet operation protects people and the environment
- System diversity 70 to 200 %
- Simple system design with the Selection Tool software

Technical Details

- For use with single- and multi-port flowboxes for independent heating/cooling operation
- Compact multi-port flowboxes with 4, 8, or 12 outlets
- Intelligent refrigerant flow management ensures optimal supply to all indoor units, regardless of their number and location in the building
- 1 inverter-controlled twin rotary compressor (8 to 14 HP)
- 1 inverter-controlled triple rotary compressor (16 to 20 HP)
- 2 inverter-controlled twin rotary compressors (22 and 24 HP)
- Outdoor unit modulation for maximum operational reliability and longevity
- Split high-efficiency heat exchangers for optimal adaptation to the outdoor temperature
- Refrigerant-cooled inverter system
- Propeller fan with high static pressure enables maximum performance with minimal noise and power consumption
- Special KO-BE-TSU or REN-KEI defrosting technology for combinations
- Short defrost cycles prevent loss of comfort in Heating operation
- Easy access to all system components
- Connection option for service tool on the outdoor or indoor unit bus
- Wireless WaveTool function simplifies commissioning, service, and system monitoring with Android/iOS smartphones
- Freely combinable with up to 121 options

HIGHER quality in LIFE

TOSHIBA

SHRMu

Technical data			MMY-UP2611FT8P-E
Capacity code	HP		26
Cooling capacity	kW	❄	73,50
Power consumption (min./nom./max.)	kW	❄	24,27
Energy efficiency EER	W/W	❄	3,02
Energy efficiency SEER		❄	7,19
Running current	A	❄	38,00
Heating capacity	kW	☀	73,50
Power consumption (min./nom./max.)	kW	☀	18,82
Energy efficiency COP	W/W	☀	3,90
Energy efficiency SCOP		☀	4,45
Running current	A	☀	29,73
Airflow	m^3/h		13500 + 12900
External static pressure	Pa		80
Sound pressure level (low/med/high)	dB(A)	❄	63
Sound pressure level (low/med/high)	dB(A)	☀	66
Sound power level	dB(A)	❄	84
Sound power level	dB(A)	☀	87
Compressor type			Twin-Rotary
Outdoor temperature operating range (min.-max.)	°C	❄	-10 / +52
Outdoor temperature operating range (min.-max.)	°C	☀	-25 / +15,5
Power supply	V/Ph+N/Hz		380-415/3+N/50
Communication line			YSLCY 2x1,5
Connectable indoor units (max.)	Pce.		58
Pipe length (max.)	m		1200
Height difference (max.)	m		90
Refrigerant			R410A
Refrigerant charge	kg		6+6
Weight	kg		2x 241

❄ Cooling ☀ Heating

The measuring conditions for this product can be found at https://www.toshiba-aircondition.com/en/measuring-conditions.html

HIGHER quality in LIFE