




HIGH-EFFICIENCY 360° CLASSIC

SMART cassette SL R32



Highlights

- SL »speed line« feature update
- Outstanding efficiency
- Customizable air distribution features
- External fresh air supply possible
- Occupancy sensor option

Highly efficient 4-way cassette for RAV single-room systems for combination exclusively with Super-Digital-Inverter outdoor units for refrigerant R32. Individual comfort, even for large spaces with high capacity requirements. Available in four capacity sizes from 5.0 to 12.5 kW.



Performance

- Very high energy efficiency
- High-performance heat exchanger
- Self-cleaning function
- Low-noise 5-stage fan
- Individual louver function
- 360° airflow
- Occupancy sensor option
- Auto diagnostic system



Flexibility

- Optimal air distribution up to room height of 4.5 m
- Easy-to-remove, washable dust filter
- Additional TCB-PCUC2E board available for external analog & digital control
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Draft Prevention Control
- Power Shift



SMART cassette SL R32 / SET

Indoor unit			RAV-HM701UT-E
Outdoor unit			RAV-GP703ATP-E
Cooling capacity	kW	❄️	6,10
Cooling range (min.-max.)	kW	❄️	1,70 - 7,00
Power consumption (min./nom./max.)	kW	❄️	- / 1,55 / -
Energy efficiency EER	W/W	❄️	3,94
Energy efficiency SEER		❄️	8,00
Energy efficiency class		❄️	A++
Outdoor temperature operating range (min.-max.)	°C	❄️	-20 / +52
Heating capacity	kW	🔥	7,00
Heating range (min.-max.)	kW	🔥	1,60 - 8,50
Power consumption (min./nom./max.)	kW	🔥	- / 1,78 / -
Energy efficiency COP	W/W	🔥	3,93
Energy efficiency SCOP		🔥	4,90
Energy efficiency class		🔥	A++
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit			RAV-HM701UT-E
Sound pressure level (low/med/high)	dB(A)	❄️	27/30/34
Sound pressure level (low/med/high)	dB(A)	🔥	27/30/34
Sound power level	dB(A)	❄️	43/46/50
Sound power level	dB(A)	🔥	43/46/50
Airflow	m³/h		810/960/1140
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		256 x 840 x 840
Weight	kg		20,0
Panel dimensions (HxWxD)	mm		30 x 950 x 950
Panel weight	kg		5,0

❄️ Cooling 🔥 Heating



SMART cassette SL R32 / SET

Outdoor unit			RAV-GP703ATP-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		13
Running current	A	❄️	6,65 - 7,25
Running current	A	🔥	7,65 - 8,35
Current consumption (nom.)	A		12,75
Current consumption (max.)	A		12,75
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	63
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	47
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		3
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m ³ /h		2250
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,35
Pre-charged up to	m		30
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 800 x300
Weight	kg		38

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

