



COST-EFFECTIVE ALTERNATIVE

## Seiya – CLASSIC 2



### Highlights

CLASSIC Line compact inverter  
A++ for cooling, A+ for heating  
Dust filter  
Infrared remote control included - WiFi-ready

Compact highwall unit from the CLASSIC SEIYA line with dust filter. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2- to 5-room multi-outdoor unit.



### Product advantages

- Good energy efficiency (A++)
- Colored, dimmable LED displays
- Low-GWP refrigerant R32
- Air as energy source in heating mode
- Compact outdoor and indoor units
- Whisper mode



### Clean indoor air

- Washable dust filters that cover the entire heat exchanger
- Dustless coil coating on the heat exchanger fins
- Self-cleaning function dries the heat exchanger at the end of operation
- Optional active carbon catechin filter strips
- Optional IAQ filter strips
- Optional Ultra Pure 2.5 filter strips



### Convenient operation

- Infrared remote control included
- WiFi-ready
- Optional APP control via smartphone or tablet
- 24 hour ON/OFF timer
- Automatic mode
- PRESET memory function
- Hi Power
- QUIET function indoor unit
- SILENT function outdoor unit, 2-stage
- Louver Swing & Fix
- 8°C Frost protection function
- Automatic restart after power failure adjustable



### WiFi special features

- All indoor units & groups On/Off control
- All indoor units & groups Weekly timer
- All indoor units & groups Setting
- Indoor temperature display
- Outdoor temperature display
- Power Select
- Child lock
- ECO operating mode
- Fireplace operating mode
- Hi-Power operating mode



## Seiya – CLASSIC 2 / SET

| Indoor unit                                     |       |   | RAS-B24B2KVG-E2 |
|-------------------------------------------------|-------|---|-----------------|
| Outdoor unit                                    |       |   | RAS-24B2AVG-E2  |
| Cooling capacity                                | kW    | ❄ | 6,50            |
| Cooling range (min.-max.)                       | kW    | ❄ | 1,10 - 7,05     |
| Power consumption (min./nom./max.)              | kW    | ❄ | 0,30/2,45/2,50  |
| Energy efficiency EER                           | W/W   | ❄ | 2,65            |
| Energy efficiency SEER                          |       | ❄ | 6,10            |
| Energy efficiency class                         |       | ❄ | A++             |
| Annual electricity consumption                  | kWh/a | ❄ | 373             |
| Outdoor temperature operating range (min.-max.) | °C    | ❄ | -15/+46         |
| Heating capacity                                | kW    | ☀ | 7,00            |
| Heating range (min.-max.)                       | kW    | ☀ | 1,20 - 7,90     |
| Power consumption (min./nom./max.)              | kW    | ☀ | 0,23/2,00/2,30  |
| Pdesign h                                       | kW    |   | 4,40            |
| Energy efficiency COP                           | W/W   | ☀ | 3,50            |
| Energy efficiency SCOP                          |       | ☀ | 4,00            |
| Energy efficiency class                         |       | ☀ | A+              |
| Annual electricity consumption                  | kWh/a | ☀ | 1539            |
| Outdoor temperature operating range (min.-max.) | °C    | ☀ | -15/+24         |

| Indoor unit                         |       |   | RAS-B24B2KVG-E2 |
|-------------------------------------|-------|---|-----------------|
| Sound pressure level (low/med/high) | dB(A) | ❄ | 29/-/48         |
| Sound pressure level (low/med/high) | dB(A) | ☀ | 29/-/48         |
| Sound power level                   | dB(A) | ❄ | 61              |
| Sound power level                   | dB(A) | ☀ | 61              |
| Airflow                             | m³/h  |   | 660-1100        |
| Condensate pipe diameter            | mm    |   | VP13            |
| Dimensions (HxWxD)                  | mm    |   | 320x1050x250    |
| Weight                              | kg    |   | 13              |

❄ Cooling ☀ Heating



## Seiya – CLASSIC 2 / SET

| Outdoor unit                        |           |    | RAS-24B2AVG-E2  |
|-------------------------------------|-----------|----|-----------------|
| Power supply                        | V/Ph+N/Hz |    | 220-240/1+N/50  |
| Recommended fusing                  | A         |    | 10              |
| Recommended power supply line type  |           |    | H07RN-F 3G1,5   |
| Communication line                  |           |    | H07RN-F 4G1,5   |
| Sound pressure level (low/med/high) | dB(A)     | ❄️ | --/--/59        |
| Sound pressure level (low/med/high) | dB(A)     | 🔥  | --/--/64        |
| Sound power level                   | dB(A)     | ❄️ | 69              |
| Sound power level                   | dB(A)     | 🔥  | 70              |
| Suction gas pipe diameter           | mm (inch) |    | 12,7 (1/2)      |
| Liquid pipe diameter                | mm (inch) |    | 6,3 (1/4)       |
| Pipe length (min.)                  | m         |    | 2               |
| Pipe length (max.)                  | m         |    | 15              |
| Height difference (max.)            | m         |    | 8               |
| Airflow                             | m³/h      |    | 2220            |
| Compressor type                     |           |    | DC Rotary       |
| Refrigerant                         |           |    | R32             |
| Refrigerant charge                  | kg        |    | 1,23            |
| Pre-charged up to                   | m         |    | 10              |
| Added refrigerant charge            | g/m       |    | 20              |
| Dimensions (HxWxD)                  | mm        |    | 550 x 780 x 290 |
| Weight                              | kg        |    | 32              |

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

| Accessories   | Description                                                                      |
|---------------|----------------------------------------------------------------------------------|
| Fernbedienung | Infrared remote control included                                                 |
| RB-RXS33-E    | Infrared remote control including weekly timer and 8°C frost protection function |
| RB-RXS34-E    | Design infrared remote control, black, with magnetic holder                      |
| RB-N105S-G    | TOSHIBA Home AC control - wireless WiFi control / Seiya Classic 2, Seiya         |
| 818F0036      | IAQ filter strips                                                                |
| 818F0023      | Active carbon-catechin filter strips                                             |
| 818F0072      | Ultra-Fresh filter strips                                                        |
| TCB-IFCB5-PE  | External on/off PCB, window contact module                                       |
| TCB-PX100-PE  | Casing for outdoor installation of window contact module for high-wall units     |

