



FOR CONFINED SPACES

Slim duct unit R32/R410A



Highlights

- Compact & slim
- Integrated drain pump
- External fresh air supply possible

Slim duct unit for RAV single-room systems for combination with Digital Inverter and Super Digital Inverter outdoor units for refrigerant R32 or R410A. Ultra-slim design with top energy-efficiency values. Available in three power levels from 2.5 to 5.0 kW.



Performance

- Extremely high energy efficiency (up to A++)
- Can be integrated unseen into false ceilings
- Self-cleaning function
- Low-noise 3-stage fan
- External static pressure can be set up to 50 Pa
- Auto diagnostic system



Flexibility

- Compatible with R32 or R410A outdoor units
- Air intake possible from below or behind
- Washable, long-life dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Low overall unit height of only 210 mm
- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- External receiver kit for infrared remote control possible
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC link
- Automatic restart setting after power outage
- Optional redundancy box available



Slim duct unit R32/R410A / SET

Indoor unit	RAV-RM561SDT-E		
Outdoor unit	RAV-GP561ATW-E		
Cooling capacity	kW	❄️	5,00
Cooling range (min.-max.)	kW	❄️	1,20 - 5,60
Power consumption (min./nom./max.)	kW	❄️	0,19/1,56/1,98
Energy efficiency EER	W/W	❄️	3,21
Energy efficiency SEER		❄️	5,77
Energy efficiency class		❄️	A+
Annual electricity consumption	kWh/a	❄️	1266
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +52
Heating capacity	kW	🔥	5,60
Heating range (min.-max.)	kW	🔥	0,90 - 7,00
Power consumption (min./nom./max.)	kW	🔥	0,16/1,58/2,66
Energy efficiency COP	W/W	🔥	3,54
Energy efficiency SCOP		🔥	4,20
Energy efficiency class		🔥	A+
Annual electricity consumption	kWh/a	🔥	1266
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit	RAV-RM561SDT-E		
Sound pressure level (low/med/high)	dB(A)	❄️	36/40/45
Sound pressure level (low/med/high)	dB(A)	🔥	36/40/45
Sound power level	dB(A)	❄️	48/53/55
Sound power level	dB(A)	🔥	48/53/55
Airflow	m ³ /h		582/678/780
External static pressure	Pa		4 - 44
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		210 x 845 x 645
Weight	kg		22

❄️ Cooling 🔥 Heating



Slim duct unit R32/R410A / SET

Outdoor unit			RAV-GP561ATW-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		16
Communication line			H07RN-F 4G1,5
Current consumption (nom.)	A		6,94
Current consumption (max.)	A		13,1
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	48
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	65
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		5
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m ³ /h		2250
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,35
Pre-charged up to	m		20
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 799 x 299
Weight	kg		45

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

Accessories	Description
RBC-AMTU31-E	Standard Wired Remote Control
RBC-AXU31-E	Infrared remote control with external receiver kit for all indoor units
TCB-FF101URE2	Spigot flange for fresh air connection Ø 100 mm

