



FOR LIMITED SPACES

Slim duct unit SL R32



Highlights

- SL »speed line« feature update
- Compact & slim
- Integrated drain pump
- External fresh air supply possible

Slim duct unit for RAV single-room systems for combination with Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Ultra-slim design with top energy-efficiency values. Available in four capacity sizes from 2.5 to 6.7 kW.



Performance

- Very high energy efficiency
- Can be integrated unseen into false ceilings
- Self-cleaning function
- Low-noise 3-stage fan
- External static pressure can be set up to 50 Pa
- Auto diagnostic system



Flexibility

- Back- or bottom air intake possible
- Washable, long-life dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- Low overall unit height of only 210 mm
- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- External receiver kit for infrared remote control possible
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Power Shift



Slim duct unit SL R32 / SET

Indoor unit			RAV-HM701SDTY-E
Outdoor unit			RAV-GP703ATP-E
Cooling capacity	kW	❄️	6,10
Cooling range (min.-max.)	kW	❄️	1,70 - 7,00
Power consumption (min./nom./max.)	kW	❄️	- / 2,03 / -
Energy efficiency EER	W/W	❄️	3,25
Energy efficiency SEER		❄️	6,20
Energy efficiency class		❄️	A++
Outdoor temperature operating range (min.-max.)	°C	❄️	-20 / +52
Heating capacity	kW	🔥	7,00
Heating range (min.-max.)	kW	🔥	1,60 - 8,00
Power consumption (min./nom./max.)	kW	🔥	- / 2,03 / -
Energy efficiency COP	W/W	🔥	3,57
Energy efficiency SCOP		🔥	4,25
Energy efficiency class		🔥	A+
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15

Indoor unit			RAV-HM701SDTY-E
Sound pressure level (low/med/high)	dB(A)	❄️	30/33/36
Sound pressure level (low/med/high)	dB(A)	🔥	30/33/36
Sound power level	dB(A)	❄️	54/57/60
Sound power level	dB(A)	🔥	54/57/60
Airflow	m³/h		860/950/1080
External static pressure	Pa		10 - 150
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		210 x 1100 x 450
Weight	kg		22

❄️ Cooling 🔥 Heating



Slim duct unit SL R32 / SET

Outdoor unit			RAV-GP703ATP-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		13
Running current	A	❄️	9,10 - 9,90
Running current	A	🔥	9,10 - 9,90
Current consumption (nom.)	A		13,22
Current consumption (max.)	A		13,22
Sound power level	dB(A)	❄️	63
Sound power level	dB(A)	🔥	63
Sound pressure level (low/med/high)	dB(A)	❄️	46
Sound pressure level (low/med/high)	dB(A)	🔥	47
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
Liquid pipe diameter	mm (inch)		6,4 (1/4)
Pipe length (min.)	m		3
Pipe length (max.)	m		50
Height difference (max.)	m		30
Airflow	m ³ /h		2250
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,35
Pre-charged up to	m		30
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		630 x 800 x300
Weight	kg		38

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

