



THE 360° CLASSIC

Standard cassette SL R32



Highlights

- SL »speed line« feature update
- Outstanding efficiency
- External fresh air supply possible
- Optional FLAT-panel
- Extensive air filter & control options

Four-way standard cassette for RAV single-room systems for combination with Digital-Inverter CLASSIC, Digital-Inverter, Super-Digital-Inverter, and Digital-Inverter BIG outdoor units for refrigerant R32. Individual comfort, even for large spaces with high capacity requirements. Available in six capacity sizes from 5.0 to 14.0 kW.



Performance

- Very high energy efficiency
- Various options are possible with FLAT panel: Plasmafilter, PM 2.5 filter, occupancy sensor, IR-receiver-kit
- High-performance heat exchanger
- Self-cleaning function dries the heat exchanger after operation
- Low-noise 3-stage fan
- Quiet function
- Auto diagnostic system



Flexibility

- Optimal air distribution up to room height of 4.6 m
- Easy-to-remove, washable dust filter
- Optional WiFi control via smartphone, tablet, or PC



Technical details

- External fresh air supply possible up to 15% of the nominal airflow
- Integrated drain pump with discharge head up to 85 cm
- Receiver for infrared remote control can be integrated
- Can be combined with all cable remote controls
- Can be integrated into VRF control systems via a TCC / TU2C link
- Compatible with TU2C link system bus
- Automatic restart setting after power outage
- Optional redundancy box available



SL SPECIAL FEATURES

- Redundancy function
- Free-Cooling control
- Support for Secondary Heating
- Air Discharge Temperature Display
- Draft Prevention Control
- Power Shift



Standard cassette SL R32 / SET

Indoor unit			RAV-HM801UTP-E
Outdoor unit			RAV-GV801ATP-E
Cooling capacity	kW	❄️	6,70
Cooling range (min.-max.)	kW	❄️	1,50 - 8,00
Power consumption (min./nom./max.)	kW	❄️	0,26/2,22/2,60
Energy efficiency EER	W/W	❄️	3,02
Energy efficiency SEER		❄️	5,81
Energy efficiency class		❄️	A+
Annual electricity consumption	kWh/a	❄️	403
Outdoor temperature operating range (min.-max.)	°C	❄️	-15 / +46
Heating capacity	kW	🔥	7,70
Heating range (min.-max.)	kW	🔥	1,50 - 9,00
Power consumption (min./nom./max.)	kW	🔥	0,26/2,13/3,03
Energy efficiency COP	W/W	🔥	3,62
Energy efficiency SCOP		🔥	4,42
Energy efficiency class		🔥	A+
Annual electricity consumption	kWh/a	🔥	1615
Outdoor temperature operating range (min.-max.)	°C	🔥	-15 / +15

Indoor unit			RAV-HM801UTP-E
Sound pressure level (low/med/high)	dB(A)	❄️	28/31/35
Sound pressure level (low/med/high)	dB(A)	🔥	28/31/35
Sound power level	dB(A)	❄️	43/46/50
Sound power level	dB(A)	🔥	43/46/50
Airflow	m ³ /h		810/960/1230
Condensate pipe diameter	mm		VP25
Dimensions (HxWxD)	mm		256 × 840 × 840
Weight	kg		20
Panel dimensions (HxWxD)	mm		30 × 950 × 950
Panel weight	kg		4,2

❄️ Cooling 🔥 Heating



Standard cassette SL R32 / SET

Outdoor unit			RAV-GV801ATP-E
Power supply	V/Ph+N/Hz		220-240/1+N/50
Recommended fusing	A		16
Recommended power supply line type			H07RN-F 3G1,5
Communication line			H07RN-F 4G1,5
Current consumption (max.)	A		15,00
Sound pressure level (low/med/high)	dB(A)	❄️	48
Sound pressure level (low/med/high)	dB(A)	🔥	51
Sound power level	dB(A)	❄️	65
Sound power level	dB(A)	🔥	68
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		5
Pipe length (max.)	m		20
Height difference (max.)	m		20
Airflow	m ³ /h		2700
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		1,40
Pre-charged up to	m		20
Added refrigerant charge	g/m		35
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		39

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

