

HIGHLY EFFICIENT ENDURANCE RUNNER

Super Digital Inverter series 3



Highlights

- Compact – durable – efficient
- Easy-install features
- Easy commissioning functions
- 3-level silent setting



Super Digital-Inverter outdoor units for RAV single-room systems with refrigerant R32, for cooling- or heating operation with a wide performance spectrum. To be combined with RAV-HM indoor units or DX-kit. Available in six capacity sizes from 5,0 to 14,0 kW cooling capacity and 5,6 to 16,0 kW heating capacity.



Performance

- Suitable for 24/7 continual operation
- Ideal for industry and for failure-critical applications
- Exceptionally high efficiency in part load range
- Controls at the lowest minimum capacities
- Small and lightweight chassis in 3 sizes
- Corresponds to the ECODESIGN Lot 10 Directive



Flexibility

- Max. pipe lengths up to 100 m
- Max. height differences up to 30 m
- Flexible control options available
- Wide operating temperature range



Technical details

- Twin rotary compressor
- Direct current hybrid inverter technology
- All units 1-phase, 230 V available
- Capacities 10, 12, 14 kW alternative 3-phase, 400V available
- Inspection window simplifies maintenance
- Kit available for noise reduction, max. capacity control, compressor operating signal
- 3-stage night operation adjustable
- Save Operation setting for demand limitation of 50% to 100%
- Built in DI/DO on board



The Super Digital Inverter system

- 100% TU2C-link compatibility
- DX kit available for connecting external heat exchangers
- Special solutions for Technical Cooling /IT
- Backup / rotation / redundancy functions
- Free Cooling Control ensures energy savings in technical cooling by utilizing outside air.
- Power Shift increases lifetime and saves energy
- Secondary Heating for controlling an additional heat source with only one remote control
- Supports new comfort remote control RBC-AMSU52-E
- Supports new comfort remote control RBC-AWSU52-E with Bluetooth functionality
- Optional WiFi control for comfort & security
- Energy monitoring via WiFi interface
- Step-by-step commissioning function
- Special Quick Service Tools
- Commissioning Mode for clear display of all sensor data
- LC Easy Monitor menu to check all sensor information
- Easy I.DN Setting for easy DN code setting
- Refrigerant amount check during test run
- Alternating defrosting for comfort & safety
- Self-test of indoor unit functions



Super Digital Inverter series 3

Technical data			RAV-GP1603AT8P-E
Cooling capacity	kW	❄️	14,00
Cooling range (min.-max.)	kW	❄️	3,10 - 16,00
Outdoor temperature operating range (min.-max.)	°C	❄️	-20 / +52
Heating capacity	kW	🔥	16,00
Heating range (min.-max.)	kW	🔥	2,60 - 18,00
Outdoor temperature operating range (min.-max.)	°C	🔥	-27 / +15
Sound power level	dB(A)	❄️	69
Sound power level	dB(A)	🔥	70
Sound pressure level (low/med/high)	dB(A)	❄️	54
Sound pressure level (low/med/high)	dB(A)	🔥	55
Suction gas pipe diameter	mm (inch)		15,9 (5/8)
Liquid pipe diameter	mm (inch)		9,5 (3/8)
Pipe length (min.)	m		3
Pipe length (max.)	m		100
Height difference (max.)	m		30
Airflow	m³/h		8800
Power supply	V/Ph+N/Hz		380-415/3+N/50
Compressor type			Twin-Rotary
Refrigerant			R32
Refrigerant charge	kg		3,50
Pre-charged up to	m		30
Added refrigerant charge	g/m		40
Dimensions (HxWxD)	mm		1640 x 1100 x 460
Weight	kg		127
SWL (LW) Night Operation, Level 1/2/3	dB(A)	❄️	60/63/66
SWL (LW) Night Operation, Level 1/2/3	dB(A)	🔥	61/64/67
SPL (Lp) Night Operation, Level 1/2/3	dB(A)	❄️	45/48/51
SPL (Lp) Night Operation, Level 1/2/3	dB(A)	🔥	46/49/52

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>

