



HIGHLY EFFICIENT FRESH AIR SUPPLY

VN heat exchanger HEXE



Highlights

- Available with register for heating/cooling function
- Free cooling possible
- Available with optional air humidification



Cross-current heat exchanger for standalone operation or for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Perfect heat recovery from the air-conditioned ambient air of up to 75%. Available in three variants: Air/Air heat exchanger, with register of 4.1 to 8.25 kW, with additional humidifier.



Performance

- High energy efficiency
- Heat recovery up to 75%
- Low-noise, 3-stage fan
- Auto diagnostic system



Flexibility

- Suitable for controlled domestic ventilation and for commercial use
- Easy-to-remove & washable heat exchanger element
- External inputs are available with an optional NRB-1HE remote adapter
- Potential-free, digital outputs as standard



Technical details

- Air humidifier, operates according to the vapor permeable film principle
- TCB-DP31HEXE drain pump optionally available
- External receiver kit for infrared remote control possible
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage



VN heat exchanger HEXE

Technical data			MMD-VNK802HEX1E
Cooling capacity	kW	❄️	6,56
Heating capacity	kW	🔥	8,61
External static pressure	Pa		85 - 105
Airflow (min./nom./max.)	m³/h		640/800/800
Airflow limit	m³/h		640 - 800
Air connections diameter	mm		250
Sound pressure level (low/med/high)	dB(A)	❄️	38/39/40
Sound pressure level (low/med/high)	dB(A)	🔥	38/39/40
Temperature exchange efficiency (min./nom./max.)	%		70/-/72,5
Enthalpy exchange efficiency (min./nom./max.)	%	❄️	56,0/-/59,0
Enthalpy exchange efficiency (min./nom./max.)	%	🔥	70,0/-/73,0
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		12,7 (½)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Heat exchanger mode power consumption (min./nom./max.)	W		350/485/530
Running current	A	❄️	1,54/2,14/2,37
Running current	A	🔥	1,54/2,14/2,37
Humidification capacity	kg/h		5,0
Humidification water pressure	bar		0,2 - 4,9
Water connection	Inch		1/2
Refrigerant			R410A
Dimensions (HxWxD)	mm		430 x 1189 x 1739
Weight	kg		111

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



R410A: Used refrigerant: R410A.



Dust filter: Washable filter against coarse contamination.



Self-cleaning function: Usage of condensate water for cleaning.

