



HIGHLY EFFICIENT FRESH AIR SUPPLY

## VN heat exchanger HEXE



### Highlights

- Available with register for heating/cooling function
- Free cooling possible
- Available with optional air humidification



Cross-current heat exchanger for standalone operation or for combination with VRF outdoor units from the MiNi-SMMS-e, SMMS-e, and SHRM-e model series. Perfect heat recovery from the air-conditioned ambient air of up to 75%. Available in three variants: Air/Air heat exchanger, with register of 4.1 to 8.25 kW, with additional humidifier.



### Performance

- High energy efficiency
- Heat recovery up to 75%
- Low-noise, 3-stage fan
- Auto diagnostic system



### Flexibility

- Suitable for controlled domestic ventilation and for commercial use
- Easy-to-remove & washable heat exchanger element
- External inputs are available with an optional NRB-1HE remote adapter
- Potential-free, digital outputs as standard



### Technical details

- Air humidifier, operates according to the vapor permeable film principle
- TCB-DP31HEXE drain pump optionally available
- External receiver kit for infrared remote control possible
- Can be combined with all cable remote controls
- Additional functions available with the RBC-AMS54E-ES remote control
- Automatic restart setting after power outage



## VN heat exchanger HEXE

Technical data			MMD-VNK1002HEX1E
Cooling capacity	kW	❄️	8,25
Heating capacity	kW	🔥	10,92
External static pressure	Pa		90 - 115
Airflow (min./nom./max.)	m³/h		820/950/950
Airflow limit	m³/h		820 - 950
Air connections diameter	mm		250
Sound pressure level (low/med/high)	dB(A)	❄️	39/41/42
Sound pressure level (low/med/high)	dB(A)	🔥	39/41/42
Temperature exchange efficiency (min./nom./max.)	%		65,5/-/67,5
Enthalpy exchange efficiency (min./nom./max.)	%	❄️	52,0/-/54,5
Enthalpy exchange efficiency (min./nom./max.)	%	🔥	66,0/-/68,5
Liquid pipe diameter	mm (inch)		6,4 (¼)
Suction gas pipe diameter	mm (inch)		12,7 (½)
Condensate pipe diameter	mm		VP25 (25/32)
Power supply	V/Ph+N/Hz		220-240/1+N/50
Heat exchanger mode power consumption (min./nom./max.)	W		520/565/575
Running current	A	❄️	2,31/2,51/2,56
Running current	A	🔥	2,31/2,51/2,56
Humidification capacity	kg/h		6,0
Humidification water pressure	bar		0,2 - 4,9
Water connection	Inch		1/2
Refrigerant			R410A
Dimensions (HxWxD)	mm		430 x 1189 x 1739
Weight	kg		112

❄️ Cooling 🔥 Heating

The measuring conditions for this product can be found at <https://www.toshiba-aircondition.com/en/measuring-conditions.html>



In order to make it easier for you to select the optimal product, you can find the description of the special TOSHIBA product functions for your model here:



**R410A:** Used refrigerant: R410A.



**Dust filter:** Washable filter against coarse contamination.



**Self-cleaning function:** Usage of condensate water for cleaning.

